



Rocky Enterprise Linux 9.2 Manual Pages on command 'lsmem.1'

C:\>man lsmem.1

LSMEM(1) User Commands LSMEM(1)

NAME

lsmem - list the ranges of available memory with their online status

SYNOPSIS

lsmem [options]

DESCRIPTION

The `lsmem` command lists the ranges of available memory with their online status.

The listed memory blocks correspond to the memory block representation in `sysfs`.

The command also shows the memory block size and the amount of memory in online and offline state.

The default output compatible with original implementation from `s390-tools`, but it's strongly recommended to avoid using default outputs in your scripts. Always explicitly define expected columns by using the `--output` option together with a columns list in environments where a stable output is required.

The `lsmem` command lists a new memory range always when the current memory block distinguish from the previous block by some output column. This default behavior is possible to override by the `--split` option (e.g. `lsmem --split=ZONES`). The special word "none" may be used to ignore all differences between memory blocks and to create as large as possible continuous ranges. The opposite semantic is `--all` to list individual memory blocks.

Note that some output columns may provide inaccurate information if a split policy forces `lsmem` to ignore differences in some attributes. For example if you merge re?

movable and non-removable memory blocks to the one range than all the range will be marked as non-removable on lsmem output.

Not all columns are supported on all systems. If an unsupported column is specified, lsmem prints the column but does not provide any data for it.

Use the --help option to see the columns description.

OPTIONS

-a, --all

List each individual memory block, instead of combining memory blocks with similar attributes.

-b, --bytes

Print the SIZE column in bytes rather than in a human-readable format.

-h, --help

Display help text and exit.

-J, --json

Use JSON output format.

-n, --noheadings

Do not print a header line.

-o, --output list

Specify which output columns to print. Use --help to get a list of all supported columns. The default list of columns may be extended if list is specified in the format +list (e.g. lsmem -o +NODE).

--output-all

Output all available columns.

-P, --pairs

Produce output in the form of key="value" pairs. All potentially unsafe characters are hex-escaped (`\x<code>`).

-r, --raw

Produce output in raw format. All potentially unsafe characters are hex-escaped (`\x<code>`).

-S, --split list

Specify which columns (attributes) use to split memory blocks to ranges.

The supported columns are STATE, REMOVABLE, NODE and ZONES, or "none". The other columns are silently ignored. For more details see DESCRIPTION

above.

-s, --sysroot directory

Gather memory data for a Linux instance other than the instance from which the `lsmem` command is issued. The specified directory is the system root of the Linux instance to be inspected.

-V, --version

Display version information and exit.

--summary[=*when*]

This option controls summary lines output. The optional argument *when* can be `never`, `always` or `only`. If the *when* argument is omitted, it defaults to `"only"`. The summary output is suppressed for `--raw`, `--pairs` and `--json`.

AUTHOR

`lsmem` was originally written by Gerald Schaefer for `s390-tools` in Perl. The C version for `util-linux` was written by Clemens von Mann, Heiko Carstens and Karel Zak.

SEE ALSO

`chmem(8)`

AVAILABILITY

The `lsmem` command is part of the `util-linux` package and is available from Linux Kernel Archive [?https://www.kernel.org/pub/linux/utils/util-linux/?](https://www.kernel.org/pub/linux/utils/util-linux/).

`util-linux`

October 2016

LSMEM(1)