



Rocky Enterprise Linux 9.2 Manual Pages on command 'lxc-user-nic.1'

C:~>man lxc-user-nic.1

lxc-user-nic(1) lxc-user-nic(1)

NAME

lxc-user-nic - Manage nics in another network namespace

SYNOPSIS

lxc-user-nic create {lxcpath} {name} {pid} {type} {bridge} {container nicname}

lxc-user-nic delete {lxcpath} {name} {path to network namespace} {type} {bridge}
{container nicname}

DESCRIPTION

lxc-user-nic is a setuid-root program with which unprivileged users may manage network interfaces for use by a lxc container.

It will consult the configuration file `/etc/lxc/lxc-usernet` to determine the number of interfaces which the calling user is allowed to create, and which bridge they may attach them to. It tracks the number of interfaces each user has created using the file `/run/lxc/nics`. It ensures that the calling user is privileged over the network namespace to which the interface will be attached. lxc-user-nic also allows one to delete network devices. Currently only ovs ports can be deleted.

OPTIONS

lxcpath

The path of the container. This is currently not used.

name The name of the container. This is currently not used.

pid The process id for the task to whose network namespace the interface should be attached.

`type` The network interface type to attach. Currently only `veth` is supported. With this type, two interfaces representing each tunnel endpoint are created. One endpoint will be attached to the specified bridge, while the other will be passed into the container.

`bridge` The bridge to which to attach the network interface, for instance `lxcbr0`.

`container nicname`

The desired interface name in the container. This will be `eth0` if unspecified.

`path to network namespace`

A path to open to get a file descriptor for the target network namespace.

This is only relevant when an `veth` device is deleted.

SEE ALSO

`lxc(1)`, `lxc-start(1)`, `lxc-usernet(5)`

AUTHOR

Christian Brauner <christian@brauner.io>

Serge Hallyn <serge@hallyn.com>

Daniel Lezcano <daniel.lezcano@free.fr>

2022-02-04

`lxc-user-nic(1)`