



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'mkdir.1'***

**C:\>man mkdir.1**

MKDIR(1)

User Commands

MKDIR(1)

### NAME

mkdir - make directories

### SYNOPSIS

mkdir [OPTION]... DIRECTORY...

### DESCRIPTION

Create the DIRECTORY(ies), if they do not already exist.

Mandatory arguments to long options are mandatory for short options too.

**-m, --mode=MODE**

set file mode (as in chmod), not a=rwx - umask

**-p, --parents**

no error if existing, make parent directories as needed

**-v, --verbose**

print a message for each created directory

**-Z** set SELinux security context of each created directory to the default type

**--context[=CTX]**

like **-Z**, or if CTX is specified then set the SELinux or SMACK security con?

text to CTX

**--help** display this help and exit

**--version**

output version information and exit

AUTHOR

Written by David MacKenzie.

## REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report mkdir translation bugs to <<https://translationproject.org/team/>>

## COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

## SEE ALSO

mkdir(2)

Full documentation at: <<https://www.gnu.org/software/coreutils/mkdir>>

or available locally via: info '(coreutils) mkdir invocation'

GNU coreutils 8.30

September 2019

MKDIR(1)