



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'mkfs.8'***

**C:\>man mkfs.8**

MKFS(8)                      System Administration                      MKFS(8)

### NAME

mkfs - build a Linux filesystem

### SYNOPSIS

mkfs [options] [-t type] [fs-options] device [size]

### DESCRIPTION

This mkfs frontend is deprecated in favour of filesystem specific mkfs.<type> utils.

mkfs is used to build a Linux filesystem on a device, usually a hard disk partition. The device argument is either the device name (e.g. /dev/hda1, /dev/sdb2), or a regular file that shall contain the filesystem. The size argument is the number of blocks to be used for the filesystem.

The exit code returned by mkfs is 0 on success and 1 on failure.

In actuality, mkfs is simply a front-end for the various filesystem builders (mkfs.fstype) available under Linux. The filesystem-specific builder is searched for via your PATH environment setting only. Please see the filesystem-specific builder manual pages for further details.

### OPTIONS

-t, --type type

Specify the type of filesystem to be built. If not specified, the default filesystem type (currently ext2) is used.

fs-options

Filesystem-specific options to be passed to the real filesystem builder.

`-V, --verbose`

Produce verbose output, including all filesystem-specific commands that are executed. Specifying this option more than once inhibits execution of any filesystem-specific commands. This is really only useful for testing.

`-V, --version`

Display version information and exit. (Option `-V` will display version information only when it is the only parameter, otherwise it will work as `--verbose`.)

`-h, --help`

Display help text and exit.

## BUGS

All generic options must precede and not be combined with filesystem-specific options. Some filesystem-specific programs do not automatically detect the device size and require the size parameter to be specified.

## AUTHORS

David Engel ([david@ods.com](mailto:david@ods.com))

Fred N. van Kempen ([waltje@uwalt.nl.mugnet.org](mailto:waltje@uwalt.nl.mugnet.org))

Ron Sommeling ([sommel@sci.kun.nl](mailto:sommel@sci.kun.nl))

The manual page was shamelessly adapted from Remy Card's version for the ext2 filesystem.

## SEE ALSO

`fs(5)`, `badblocks(8)`, `fsck(8)`, `mkdosfs(8)`, `mke2fs(8)`, `mkfs.bfs(8)`, `mkfs.ext2(8)`, `mkfs.ext3(8)`, `mkfs.ext4(8)`, `mkfs.minix(8)`, `mkfs.msdos(8)`, `mkfs.vfat(8)`, `mkfs.xfs(8)`

## AVAILABILITY

The `mkfs` command is part of the `util-linux` package and is available from <https://www.kernel.org/pub/linux/utils/util-linux/>.

util-linux

June 2011

MKFS(8)