



Rocky Enterprise Linux 9.2 Manual Pages on command 'mktemp.1'

C:\>man mktemp.1

MKTEMP(1) User Commands MKTEMP(1)

NAME

mktemp - create a temporary file or directory

SYNOPSIS

mktemp [OPTION]... [TEMPLATE]

DESCRIPTION

Create a temporary file or directory, safely, and print its name. TEMPLATE must contain at least 3 consecutive 'X's in last component. If TEMPLATE is not specified, use tmp.XXXXXXXXXX, and --tmpdir is implied. Files are created u+rw, and directories u+rwx, minus umask restrictions.

-d, --directory

create a directory, not a file

-u, --dry-run

do not create anything; merely print a name (unsafe)

-q, --quiet

suppress diagnostics about file/dir-creation failure

--suffix=SUFF

append SUFF to TEMPLATE; SUFF must not contain a slash. This option is implied if TEMPLATE does not end in X

-p DIR, --tmpdir[=DIR]

interpret TEMPLATE relative to DIR; if DIR is not specified, use \$TMPDIR if set, else /tmp. With this option, TEMPLATE must not be an absolute name;

unlike with `-t`, `TEMPLATE` may contain slashes, but `mktemp` creates only the final component

`-t` interpret `TEMPLATE` as a single file name component, relative to a directory:

`$TMPDIR`, if set; else the directory specified via `-p`; else `/tmp` [deprecated]

`--help` display this help and exit

`--version`

output version information and exit

AUTHOR

Written by Jim Meyering and Eric Blake.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report `mktemp` translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

`mkstemp(3)`, `mkdtemp(3)`, `mktemp(3)`

Full documentation at: <<https://www.gnu.org/software/coreutils/mktemp>>

or available locally via: `info '(coreutils) mktemp invocation'`