



Rocky Enterprise Linux 9.2 Manual Pages on command 'mpath_persistent_reserve_in.3'

C:\>man mpath_persistent_reserve_in.3

MPATH_PERSISTENT_RESERVE_IN(3) Library Functions Manual MPATH_PERSISTENT_RESERVE_IN(3)

NAME

mpath_persistent_reserve_in - send PRIN command to DM device

SYNOPSIS

```
#include <mpath_persist.h>
```

```
int mpath_persistent_reserve_in(int fd, int rq_servact, struct prin_resp *resp, int  
noisy, int verbose)
```

DESCRIPTION

The function in the `mpath_persistent_reserve_in ()` sends PRIN command to the DM device and gets the response.

Parameters:

`fd` The file descriptor of a multipath device. Input argument.

`rq_servact` PRIN command service action. Input argument.

`resp` The response from PRIN service action. The caller should manage the memory allocation of this structure.

`noisy` Turn on debugging trace: Input argument. 0->Disable, 1->Enable.

`verbose` Set verbosity level. Input argument. value:[0-3]. 0->Crits and Errors, 1->Warnings, 2->Info, 3->Debug.

RETURNS

MPATH_PR_SUCCESS

If PR command successful.

MPATH_PR_SYNTAX_ERROR

If syntax error or invalid parameter.

MPATH_PR_SENSE_NOT_READY

If command fails with [sk,asc,ascq: 0x2,*,*].

MPATH_PR_SENSE_MEDIUM_ERROR

If command fails with [sk,asc,ascq: 0x3,*,*].

MPATH_PR_SENSE_HARDWARE_ERROR

If command fails with [sk,asc,ascq: 0x4,*,*].

MPATH_PR_SENSE_INVALID_OP

If command fails with [sk,asc,ascq: 0x5,0x20,0x0].

MPATH_PR_ILLEGAL_REQ

If command fails with [sk,asc,ascq: 0x5,*,*].

MPATH_PR_SENSE_UNIT_ATTENTION

If command fails with [sk,asc,ascq: 0x6,*,*].

MPATH_PR_SENSE_ABORTED_COMMAND

If command fails with [sk,asc,ascq: 0xb,*,*].

MPATH_PR_NO_SENSE

If command fails with [sk,asc,ascq: 0x0,*,*].

MPATH_PR_SENSE_MALFORMED

If command fails with SCSI command malformed.

MPATH_PR_FILE_ERROR

If command fails while accessing file (device node) problems(e.g. not found).

MPATH_PR_DMMP_ERROR

If Device Mapper related error.(e.g Error in getting dm info).

MPATH_PR_OTHER

If other error/warning has occurred(e.g transport or driver error).

SEE ALSO

mpathpersist(8).

AUTHORS

multipath-tools was developed by Christophe Varoqui <christophe.varoqui@opensvc.com> and others.