



Rocky Enterprise Linux 9.2 Manual Pages on command 'mq_getattr.3'

C:\>man mq_getattr.3

MQ_GETATTR(3) Linux Programmer's Manual MQ_GETATTR(3)

NAME

mq_getattr, mq_setattr - get/set message queue attributes

SYNOPSIS

```
#include <mqueue.h>

int mq_getattr(mqd_t mqdes, struct mq_attr *attr);

int mq_setattr(mqd_t mqdes, const struct mq_attr *newattr,
               struct mq_attr *oldattr);
```

Link with -lrt.

DESCRIPTION

mq_getattr() and mq_setattr() respectively retrieve and modify attributes of the message queue referred to by the message queue descriptor mqdes.

mq_getattr() returns an mq_attr structure in the buffer pointed by attr. This structure is defined as:

```
struct mq_attr {
    long mq_flags;     /* Flags: 0 or O_NONBLOCK */
    long mq_maxmsg;    /* Max. # of messages on queue */
    long mq_msgsize;   /* Max. message size (bytes) */
    long mq_curmsgs;   /* # of messages currently in queue */
};
```

The mq_flags field contains flags associated with the open message queue description. This field is initialized when the queue is created by mq_open(3). The only

flag that can appear in this field is O_NONBLOCK.

The mq_maxmsg and mq_msgsize fields are set when the message queue is created by mq_open(3). The mq_maxmsg field is an upper limit on the number of messages that may be placed on the queue using mq_send(3). The mq_msgsize field is an upper limit on the size of messages that may be placed on the queue. Both of these fields must have a value greater than zero. Two /proc files that place ceilings on the values for these fields are described in mq_overview(7).

The mq_curmsgs field returns the number of messages currently held in the queue. mq_setattr() sets message queue attributes using information supplied in the mq_attr structure pointed to by newattr. The only attribute that can be modified is the setting of the O_NONBLOCK flag in mq_flags. The other fields in newattr are ignored. If the oldattr field is not NULL, then the buffer that it points to is used to return an mq_attr structure that contains the same information that is returned by mq_getattr().

RETURN VALUE

On success mq_getattr() and mq_setattr() return 0; on error, -1 is returned, with errno set to indicate the error.

ERRORS

- EBADF The message queue descriptor specified in mqdes is invalid.
- EINVAL newattr->mq_flags contained set bits other than O_NONBLOCK.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?mq_getattr(), mq_setattr() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

On Linux, mq_getattr() and mq_setattr() are library functions layered on top of the mq_getsetattr(2) system call.

EXAMPLE

The program below can be used to show the default `mq_maxmsg` and `mq_msgsize` values that are assigned to a message queue that is created with a call to `mq_open(3)` in which the `attr` argument is `NULL`. Here is an example run of the program:

```
$. /a.out /testq
Maximum # of messages on queue: 10
Maximum message size:      8192
```

Since Linux 3.5, the following `/proc` files (described in `mq_overview(7)`) can be used to control the defaults:

```
$ uname -sr
Linux 3.8.0
$ cat /proc/sys/fs/mqueue/msg_default
10
$ cat /proc/sys/fs/mqueue/msgsize_default
8192
```

Program source

```
#include <mqueue.h>
#include <sys/stat.h>
#include <fcntl.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

#define errExit(msg) do { perror(msg); exit(EXIT_FAILURE); \
                        } while (0)

int
main(int argc, char *argv[])
{
    mqd_t mqd;
    struct mq_attr attr;

    if (argc != 2) {
        fprintf(stderr, "Usage: %s mq-name\n", argv[0]);
        exit(EXIT_FAILURE);
    }

    mqd = mq_open(argv[1], O_CREAT | O_EXCL, S_IRUSR | S_IWUSR, NULL);
```

```
if (mqd == (mqd_t) -1)
    errExit("mq_open");
if (mq_getattr(mqd, &attr) == -1)
    errExit("mq_getattr");
printf("Maximum # of messages on queue: %ld\n", attr.mq_maxmsg);
printf("Maximum message size:          %ld\n", attr.mq_msgsize);
if (mq_unlink(argv[1]) == -1)
    errExit("mq_unlink");
exit(EXIT_SUCCESS);
}
```

SEE ALSO

mq_close(3), mq_notify(3), mq_open(3), mq_receive(3), mq_send(3), mq_unlink(3),
mq_overview(7)

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.