



## Rocky Enterprise Linux 9.2 Manual Pages on command 'mq\_unlink.3'

C:\>man mq\_unlink.3

MQ\_UNLINK(3)                   Linux Programmer's Manual                   MQ\_UNLINK(3)

### NAME

mq\_unlink - remove a message queue

### SYNOPSIS

```
#include <mqueue.h>
```

```
int mq_unlink(const char *name);
```

Link with -lrt.

### DESCRIPTION

mq\_unlink() removes the specified message queue name. The message queue name is removed immediately. The queue itself is destroyed once any other processes that have the queue open close their descriptors referring to the queue.

### RETURN VALUE

On success mq\_unlink() returns 0; on error, -1 is returned, with errno set to indicate the error.

### ERRORS

EACCES The caller does not have permission to unlink this message queue.

ENAMETOOLONG

name was too long.

ENOENT There is no message queue with the given name.

### ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?mq\_unlink() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

SEE ALSO

mq\_close(3), mq\_getattr(3), mq\_notify(3), mq\_open(3), mq\_receive(3), mq\_send(3),  
mq\_overview(7)

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux 2015-08-08 MQ\_UNLINK(3)