



## **Rocky Enterprise Linux 9.2 Manual Pages on command 'msgctl.2'**

**C:\>man msgctl.2**

MSGCTL(2)                   Linux Programmer's Manual                   MSGCTL(2)

### NAME

msgctl - System V message control operations

### SYNOPSIS

```
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/msg.h>

int msgctl(int msqid, int cmd, struct msqid_ds *buf);
```

### DESCRIPTION

msgctl() performs the control operation specified by cmd on the System V message queue with identifier msqid.

The msqid\_ds data structure is defined in <sys/msg.h> as follows:

```
struct msqid_ds {
    struct ipc_perm msg_perm; /* Ownership and permissions */
    time_t      msg_stime; /* Time of last msgsnd(2) */
    time_t      msg_rtime; /* Time of last msgrcv(2) */
    time_t      msg_ctime; /* Time of last change */
    unsigned long __msg_cbytes; /* Current number of bytes in
                                queue (nonstandard) */
    msgqnum_t   msg_qnum; /* Current number of messages
                            in queue */
    msglen_t    msg_qbytes; /* Maximum number of bytes
```

```

                allowed in queue */
pid_t      msg_lspid; /* PID of last msgsnd(2) */
pid_t      msg_lrpid; /* PID of last msgrcv(2) */
};

```

The ipc\_perm structure is defined as follows (the highlighted fields are settable using IPC\_SET):

```

struct ipc_perm {
    key_t      __key; /* Key supplied to msgget(2) */
    uid_t      uid; /* Effective UID of owner */
    gid_t      gid; /* Effective GID of owner */
    uid_t      cuid; /* Effective UID of creator */
    gid_t      cgid; /* Effective GID of creator */
    unsigned short mode; /* Permissions */
    unsigned short __seq; /* Sequence number */
};

```

Valid values for cmd are:

#### IPC\_STAT

Copy information from the kernel data structure associated with msgqid into the msgqid\_ds structure pointed to by buf. The caller must have read permission on the message queue.

#### IPC\_SET

Write the values of some members of the msgqid\_ds structure pointed to by buf to the kernel data structure associated with this message queue, updating also its msg\_ctime member. The following members of the structure are updated: msg\_qbytes, msg\_perm.uid, msg\_perm.gid, and (the least significant 9 bits of) msg\_perm.mode. The effective UID of the calling process must match the owner (msg\_perm.uid) or creator (msg\_perm.cuid) of the message queue, or the caller must be privileged. Appropriate privilege (Linux: the CAP\_SYS\_RESOURCE capability) is required to raise the msg\_qbytes value beyond the system parameter MSGMNB.

#### IPC\_RMID

Immediately remove the message queue, awakening all waiting reader and writer processes (with an error return and errno set to EIDRM). The calling

process must have appropriate privileges or its effective user ID must be either that of the creator or owner of the message queue. The third argument to `msgctl()` is ignored in this case.

#### IPC\_INFO (Linux-specific)

Return information about system-wide message queue limits and parameters in the structure pointed to by `buf`. This structure is of type `msginfo` (thus, a cast is required), defined in `<sys/msg.h>` if the `_GNU_SOURCE` feature test macro is defined:

```
struct msginfo {
    int msgpool; /* Size in kibibytes of buffer pool
                 used to hold message data;
                 unused within kernel */
    int msgmap; /* Maximum number of entries in message
                 map; unused within kernel */
    int msgmax; /* Maximum number of bytes that can be
                 written in a single message */
    int msgmnb; /* Maximum number of bytes that can be
                 written to queue; used to initialize
                 msg_qbytes during queue creation
                 (msgget(2)) */
    int msgmni; /* Maximum number of message queues */
    int msgssz; /* Message segment size;
                 unused within kernel */
    int msgtql; /* Maximum number of messages on all queues
                 in system; unused within kernel */
    unsigned short int msgseg;
                 /* Maximum number of segments;
                 unused within kernel */
};
```

The `msgmni`, `msgmax`, and `msgmnb` settings can be changed via `/proc` files of the same name; see `proc(5)` for details.

#### MSG\_INFO (Linux-specific)

Return a `msginfo` structure containing the same information as for `IPC_INFO`,

except that the following fields are returned with information about system resources consumed by message queues: the `msgpool` field returns the number of message queues that currently exist on the system; the `msgmap` field returns the total number of messages in all queues on the system; and the `msgsz` field returns the total number of bytes in all messages in all queues on the system.

#### MSG\_STAT (Linux-specific)

Return a `msqid_ds` structure as for `IPC_STAT`. However, the `msqid` argument is not a queue identifier, but instead an index into the kernel's internal array that maintains information about all message queues on the system.

#### MSG\_STAT\_ANY (Linux-specific, since Linux 4.17)

Return a `msqid_ds` structure as for `MSG_STAT`. However, `msg_perm.mode` is not checked for read access for `msqid` meaning that any user can employ this operation (just as any user may read `/proc/sysvipc/msg` to obtain the same information).

#### RETURN VALUE

On success, `IPC_STAT`, `IPC_SET`, and `IPC_RMID` return 0. A successful `IPC_INFO` or `MSG_INFO` operation returns the index of the highest used entry in the kernel's internal array recording information about all message queues. (This information can be used with repeated `MSG_STAT` or `MSG_STAT_ANY` operations to obtain information about all queues on the system.) A successful `MSG_STAT` or `MSG_STAT_ANY` operation returns the identifier of the queue whose index was given in `msqid`.

On error, -1 is returned with `errno` indicating the error.

#### ERRORS

On failure, `errno` is set to one of the following:

**EACCES** The argument `cmd` is equal to `IPC_STAT` or `MSG_STAT`, but the calling process does not have read permission on the message queue `msqid`, and does not have the `CAP_IPC_OWNER` capability in the user namespace that governs its IPC namespace.

**EFAULT** The argument `cmd` has the value `IPC_SET` or `IPC_STAT`, but the address pointed to by `buf` isn't accessible.

**EIDRM** The message queue was removed.

**EINVAL** Invalid value for `cmd` or `msqid`. Or: for a `MSG_STAT` operation, the index

value specified in `msqid` referred to an array slot that is currently unused.

**EPERM** The argument `cmd` has the value `IPC_SET` or `IPC_RMID`, but the effective user ID of the calling process is not the creator (as found in `msg_perm.cuid`) or the owner (as found in `msg_perm.uid`) of the message queue, and the caller is not privileged (Linux: does not have the `CAP_SYS_ADMIN` capability).

**EPERM** An attempt (`IPC_SET`) was made to increase `msg_qbytes` beyond the system parameter `MSGMNB`, but the caller is not privileged (Linux: does not have the `CAP_SYS_RESOURCE` capability).

## CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SVr4.

## NOTES

The inclusion of `<sys/types.h>` and `<sys/ipc.h>` isn't required on Linux or by any version of POSIX. However, some old implementations required the inclusion of these header files, and the SVID also documented their inclusion. Applications intended to be portable to such old systems may need to include these header files.

The `IPC_INFO`, `MSG_STAT` and `MSG_INFO` operations are used by the `ipcs(1)` program to provide information on allocated resources. In the future these may be moved or moved to a `/proc` filesystem interface.

Various fields in the struct `msqid_ds` were typed as `short` under Linux 2.2 and have become `long` under Linux 2.4. To take advantage of this, a recompilation under `glibc-2.1.91` or later should suffice. (The kernel distinguishes old and new calls by an `IPC_64` flag in `cmd`.)

## SEE ALSO

`msgget(2)`, `msgrcv(2)`, `msgsnd(2)`, `capabilities(7)`, `mq_overview(7)`, `sysvipc(7)`

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.