



Rocky Enterprise Linux 9.2 Manual Pages on command 'msgfmt.1'

C:\>man msgfmt.1

MSGFMT(1) GNU MSGFMT(1)

NAME

msgfmt - compile message catalog to binary format

SYNOPSIS

msgfmt [OPTION] filename.po ...

DESCRIPTION

Generate binary message catalog from textual translation description.

Mandatory arguments to long options are mandatory for short options too. Similarly for optional arguments.

Input file location:

filename.po ...

input files

-D, --directory=DIRECTORY

add DIRECTORY to list for input files search

If input file is -, standard input is read.

Operation mode:

-j, --java

Java mode: generate a Java ResourceBundle class

--java2

like --java, and assume Java2 (JDK 1.2 or higher)

--csharp

C# mode: generate a .NET .dll file

--csharp-resources

C# resources mode: generate a .NET .resources file

--tcl Tcl mode: generate a tcl/msgcat .msg file

--qt Qt mode: generate a Qt .qm file

--desktop

Desktop Entry mode: generate a .desktop file

--xml XML mode: generate XML file

Output file location:

-o, --output-file=FILE

write output to specified file

--strict

enable strict Uniform mode

If output file is -, output is written to standard output.

Output file location in Java mode:

-r, --resource=RESOURCE

resource name

-l, --locale=LOCALE

locale name, either language or language_COUNTRY

--source

produce a .java file, instead of a .class file

-d DIRECTORY

base directory of classes directory hierarchy

The class name is determined by appending the locale name to the resource name, separated with an underscore. The -d option is mandatory. The class is written under the specified directory.

Output file location in C# mode:

-r, --resource=RESOURCE

resource name

-l, --locale=LOCALE

locale name, either language or language_COUNTRY

-d DIRECTORY

base directory for locale dependent .dll files

The -l and -d options are mandatory. The .dll file is written in a subdirectory of

the specified directory whose name depends on the locale.

Output file location in Tcl mode:

`-l, --locale=LOCALE`

locale name, either language or language_COUNTRY

`-d DIRECTORY`

base directory of .msg message catalogs

The `-l` and `-d` options are mandatory. The .msg file is written in the specified directory.

Desktop Entry mode options:

`-l, --locale=LOCALE`

locale name, either language or language_COUNTRY

`-o, --output-file=FILE`

write output to specified file

`--template=TEMPLATE`

a .desktop file used as a template

`-d DIRECTORY`

base directory of .po files

`-kWORD, --keyword=WORD`

look for WORD as an additional keyword

`-k, --keyword`

do not to use default keywords

The `-l`, `-o`, and `--template` options are mandatory. If `-D` is specified, input files are read from the directory instead of the command line arguments.

XML mode options:

`-l, --locale=LOCALE`

locale name, either language or language_COUNTRY

`-L, --language=NAME`

recognise the specified XML language

`-o, --output-file=FILE`

write output to specified file

`--template=TEMPLATE`

an XML file used as a template

`-d DIRECTORY`

base directory of .po files

The -l, -o, and --template options are mandatory. If -D is specified, input files are read from the directory instead of the command line arguments.

Input file syntax:

-P, --properties-input

input files are in Java .properties syntax

--stringtable-input

input files are in NeXTstep/GNUstep .strings syntax

Input file interpretation:

-c, --check

perform all the checks implied by --check-format, --check-header, --check-domain

--check-format

check language dependent format strings

--check-header

verify presence and contents of the header entry

--check-domain

check for conflicts between domain directives and the --output-file option

-C, --check-compatibility

check that GNU msgfmt behaves like X/Open msgfmt

--check-accelerators[=CHAR]

check presence of keyboard accelerators for menu items

-f, --use-fuzzy

use fuzzy entries in output

Output details:

-a, --alignment=NUMBER

align strings to NUMBER bytes (default: 1)

--endianness=BYTEORDER

write out 32-bit numbers in the given byte order (big or little, default depends on platform)

--no-hash

binary file will not include the hash table

Informative output:

-h, --help

display this help and exit

-V, --version

output version information and exit

--statistics

print statistics about translations

-v, --verbose

increase verbosity level

AUTHOR

Written by Ulrich Drepper.

REPORTING BUGS

Report bugs to <bug-gnu-gettext@gnu.org>.

COPYRIGHT

Copyright ? 1995-1998, 2000-2016 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO

WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for msgfmt is maintained as a Texinfo manual. If the info

and msgfmt programs are properly installed at your site, the command

info msgfmt

should give you access to the complete manual.

GNU gettext-tools 0.19.8.1

June 2016

MSGFMT(1)