



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ngettext.1'***

**C:\>man ngettext.1**

NGGETTEXT(1) GNU NGGETTEXT(1)

### NAME

ngettext - translate message and choose plural form

### SYNOPSIS

ngettext [OPTION] [TEXTDOMAIN] MSGID MSGID-PLURAL COUNT

### DESCRIPTION

The `ngettext` program translates a natural language message into the user's language, by looking up the translation in a message catalog, and chooses the appropriate plural form, which depends on the number `COUNT` and the language of the message catalog where the translation was found.

Display native language translation of a textual message whose grammatical form depends on a number.

`-d, --domain=TEXTDOMAIN`

retrieve translated message from `TEXTDOMAIN`

`-e` enable expansion of some escape sequences

`-E` (ignored for compatibility)

`-h, --help`

display this help and exit

`-V, --version`

display version information and exit

`[TEXTDOMAIN]`

retrieve translated message from `TEXTDOMAIN`

## MSGID MSGID-PLURAL

translate MSGID (singular) / MSGID-PLURAL (plural)

COUNT choose singular/plural form based on this value

If the TEXTDOMAIN parameter is not given, the domain is determined from the environment variable TEXTDOMAIN. If the message catalog is not found in the regular directory, another location can be specified with the environment variable TEXTDOMAIN. Standard search directory: /usr/share/locale

## AUTHOR

Written by Ulrich Drepper.

## REPORTING BUGS

Report bugs to <bug-gnu-gettext@gnu.org>.

## COPYRIGHT

Copyright ? 1995-1997, 2000-2007 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

## SEE ALSO

The full documentation for ngettext is maintained as a Texinfo manual. If the info and ngettext programs are properly installed at your site, the command

info ngettext

should give you access to the complete manual.