



Rocky Enterprise Linux 9.2 Manual Pages on command 'padsd.1'

C:\>man padsd.1

padsd(1) General Commands Manual padsd(1)

NAME

padsd - PulseAudio OSS Wrapper

SYNOPSIS

padsd [options] PROGRAM [ARGUMENTS ...]

padsd -h

DESCRIPTION

padsd starts the specified program and redirects its access to OSS compatible audio devices (/dev/dsp and auxiliary devices) to a PulseAudio sound server.

padsd uses the \$LD_PRELOAD environment variable that is interpreted by ld.so(8) and thus does not work for SUID binaries and statically built executables.

Equivalent to using padsd is starting an application with \$LD_PRELOAD set to libpulsdsp.so

OPTIONS

-h | --help

Show help.

-s SERVER

Set the PulseAudio server to connect to.

-n NAME

The client application name that shall be passed to the server when connect?

ing.

-m NAME

The stream name that shall be passed to the server when creating a stream.

- M Disable /dev/mixer emulation.
- S Disable /dev/sndstat emulation.
- D Disable /dev/dsp emulation.
- d Enable debug output.

AUTHORS

The PulseAudio Developers <pulseaudio-discuss (at) lists (dot) freedesktop (dot) org>; PulseAudio is available from <http://pulseaudio.org/>

SEE ALSO

[pulseaudio\(1\)](#), [pasuspender\(1\)](#), [ld.so\(8\)](#)

Manuals

User

[padsp\(1\)](#)