



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'pidof.8'***

**C:\>man pidof.8**

PIDOF(8)                      Linux System Administrator's Manual                      PIDOF(8)

### NAME

pidof -- find the process ID of a running program.

### SYNOPSIS

```
pidof [-s] [-c] [-n] [-x] [-z] [-o omitpid[,omitpid...]] [-o omitpid[,omit?
pid...]] [-d sep] program [program...]
```

### DESCRIPTION

Pidof finds the process id's (PIDs) of the named programs. It prints those id's on the standard output. This program is on some systems used in run-level change scripts, especially when the system has a System-V like rc structure. In that case these scripts are located in /etc/rc?.d, where ? is the runlevel. If the system has a start-stop-daemon (8) program that should be used instead.

### OPTIONS

- s    Single shot - this instructs the program to only return one pid.
  
- c    Only return process PIDs that are running with the same root directory. This option is ignored for non-root users, as they will be unable to check the current root directory of processes they do not own.

- n Avoid stat(2) system function call on all binaries which are located on network based file systems like NFS. Instead of using this option the variable PIDOF\_NETFS may be set and exported.
- q Do not display matched PIDs to standard out. Simply exit with a status of true or false to indicate whether a matching PID was found.
- x Scripts too - this causes the program to also return process id's of shells running the named scripts.
- z Try to detect processes which are stuck in uninterruptible (D) or zombie (Z) status. Usually these processes are skipped as trying to deal with them can cause pidof to hang.
- d sep Tells pidof to use sep as an output separator if more than one PID is shown. The default separator is a space.
- o omitpid Tells pidof to omit processes with that process id. The special pid %PPID can be used to name the parent process of the pidof program, in other words the calling shell or shell script.

## EXIT STATUS

- 0 At least one program was found with the requested name.
- 1 No program was found with the requested name.

## NOTES

pidof is actually the same program as killall5; the program behaves according to the name under which it is called.

When pidof is invoked with a full pathname to the program it should find the pid

of, it is reasonably safe. Otherwise it is possible that it returns PIDs of running programs that happen to have the same name as the program you're after but are actually other programs. Note that the executable name of running processes is calculated with `readlink(2)`, so symbolic links to executables will also match.

Zombie processes or processes in disk sleep (states Z and D, respectively) are ignored, as attempts to access the stats of these will sometimes fail. The `-z` flag (see above) tells `pidof` to try to detect these sleeping and zombie processes, at the risk of failing or hanging.

#### SEE ALSO

`shutdown(8)`, `init(8)`, `halt(8)`, `reboot(8)`, `killall5(8)`

#### AUTHOR

Miquel van Smoorenburg, [miquels@cistron.nl](mailto:miquels@cistron.nl)

01 Sep 1998

PIDOF(8)