

disconnect when ip-up finishes running. This function is only available to the root user.

poff

poff closes a PPP connection. If more than one PPP connection exists, the one named in the argument to poff will be killed, e.g.

```
poff myprovider2
```

will terminate the connection to myprovider2, and leave the PPP connections to e.g. "myprovider1" or "myprovider3" up and running.

poff takes the following command line options:

- r causes the connection to be redialed after it is dropped.
- d toggles the state of pppd's debug option.
- c causes pppd(8) to renegotiate compression.
- a stops all running ppp connections. If the argument isp-name is given it will be ignored.
- h displays help information.
- v prints the version and exits.

If no argument is given, poff will stop or signal pppd if and only if there is exactly one running. If more than one connection is active, it will exit with an error code of 1.

plog

plog shows you the last few lines of /var/log/ppp.log. If that file doesn't exist, it shows you the last few lines of your /var/log/syslog file, but excluding the lines not generated by pppd. This script makes use of the tail(1) command, so arguments that can be passed to tail(1) can also be passed to plog.

Note: the plog script can only be used by root or another system administrator in group "adm", due to security reasons. Also, to have all pppd-generated information in one logfile, that plog can show, you need the following line in your /etc/sys?

log.conf file:

```
local2.*    -/var/log/ppp.log
```

FILES

/etc/ppp/options

PPPd system options file.

/etc/ppp/pap-secrets

System PAP passwords file.

/etc/ppp/chap-secrets

System CHAP passwords file.

/etc/ppp/peers/

Directory holding the peer options files. The default file is called provider.

/etc/chatscripts/provider

The chat script invoked from the default /etc/ppp/peers/provider.

/var/log/ppp.log

The default PPP log file.

AUTHORS

The p-commands were written by Christoph Lameter <clameter@debian.org>. Updated and revised by Philip Hands <phil@hands.com>.

This manual was written by Othmar Pasteka <othmar@tron.at>. Modified by Rob Levin <lilo@openprojects.net>, with some extensions taken from the old p-commands manual written by John Hasler <jhasler@debian.org>.

SEE ALSO

pppd(8), chat(8), tail(1).

Debian Project

July 2000

PON(1)