



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'popularity-contest.8'***

**C:\>man popularity-contest.8**

POPULARITY-CONTEST(8)

POPULARITY-CONTEST(8)

### NAME

popularity-contest - list the most popular Debian packages

### SYNOPSIS

popularity-contest

### DESCRIPTION

The `popularity-contest` command gathers information about Debian packages installed on the system, and prints the name of the most recently used executable program in that package as well as its last-accessed time (`atime`) and last-attribute-changed time (`ctime`) to stdout.

When aggregated with the output of `popularity-contest` from many other systems, this information is valuable because it can be used to determine which Debian packages are commonly installed, used, or installed and never used. This helps Debian maintainers make decisions such as which packages should be installed by default on new systems.

The resulting statistic is available from the project home page <https://popcon.debian.org/>.

Normally, `popularity-contest` is run from a `cron(8)` job, `/etc/cron.daily/popularity-contest`, which automatically submits the results to Debian package maintainers (only once a week) according to the settings in `/etc/popularity-contest.conf` and `/usr/share/popularity-contest/default.conf`.

SEE ALSO

The popularity-contest FAQ at /usr/share/doc/popularity-contest/FAQ pop?  
con-largest-unused(8), cron(8)

Additional documentation is in /usr/share/doc/popularity-contest/.

#### AUTHOR

Avery Pennarun <apenwarr@debian.org>.

Debian/GNU Linux

November 2001

POPULARITY-CONTEST(8)