



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'psfxtable.1'***

**C:\>man psfxtable.1**

PSFXTABLE(1)                    General Commands Manual                    PSFXTABLE(1)

### NAME

psfxtable - handle Unicode character tables for console fonts

### SYNOPSIS

psfxtable [-i infont] [-o outfont] [-it intable] [-ot outtable] [-nt]

### DESCRIPTION

psfxtable handles the embedded Unicode character table for .psf format console fonts. It reads a font and possibly a table and writes a font and/or a table. psfaddtable(1), psfgettext(1) and psfstriptable(1) are links to it.

Each of the filenames infont, outfont, intable, and outtable may be replaced by a single dash (-), in which case standard input or standard output is used. If no -i option is given, the font is read from standard input. If no -it or -o or -ot option is given, no input table is read or no output font or output table is written.

By default the output font (if any) will have a Unicode table when either the input font has one, or an explicit table (which overrides an input font table) has been provided. The option -nt causes output of a font without table. When outfont is requested it will get a psf1 header when infont has a psf1 header and intable does not have sequences and a psf2 header otherwise.

### SEE ALSO

setfont(8), psfaddtable(1), psfgettext(1), psfstriptable(1)