



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'pthread\_setname\_np.3'***

**C:\>man pthread\_setname\_np.3**

PTHREAD\_SETNAME\_NP(3)      Linux Programmer's Manual      PTHREAD\_SETNAME\_NP(3)

### NAME

pthread\_setname\_np, pthread\_getname\_np - set/get the name of a thread

### SYNOPSIS

```
#define _GNU_SOURCE      /* See feature_test_macros(7) */
#include <pthread.h>
int pthread_setname_np(pthread_t thread, const char *name);
int pthread_getname_np(pthread_t thread,
                        char *name, size_t len);
```

Compile and link with -pthread.

### DESCRIPTION

By default, all the threads created using pthread\_create() inherit the program name. The pthread\_setname\_np() function can be used to set a unique name for a thread, which can be useful for debugging multithreaded applications. The thread name is a meaningful C language string, whose length is restricted to 16 characters, including the terminating null byte ('\0'). The thread argument specifies the thread whose name is to be changed; name specifies the new name.

The pthread\_getname\_np() function can be used to retrieve the name of the thread. The thread argument specifies the thread whose name is to be retrieved. The buffer name is used to return the thread name; len specifies the number of bytes available in name. The buffer specified by name should be at least 16 characters in length.

The returned thread name in the output buffer will be null terminated.

## RETURN VALUE

On success, these functions return 0; on error, they return a nonzero error number.

## ERRORS

The `pthread_setname_np()` function can fail with the following error:

ERANGE The length of the string specified pointed to by `name` exceeds the allowed limit.

The `pthread_getname_np()` function can fail with the following error:

ERANGE The buffer specified by `name` and `len` is too small to hold the thread name.

If either of these functions fails to open `/proc/self/task/[tid]/comm`, then the call may fail with one of the errors described in `open(2)`.

## VERSIONS

These functions first appeared in glibc in version 2.12.

## ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`pthread_setname_np()`, ? Thread safety ? MT-Safe ?

?`pthread_getname_np()` ? ? ?

??

## CONFORMING TO

These functions are nonstandard GNU extensions; hence the suffix `"_np"` (non-portable) in the names.

## NOTES

`pthread_setname_np()` internally writes to the thread-specific `comm` file under the `/proc` filesystem: `/proc/self/task/[tid]/comm`. `pthread_getname_np()` retrieves it from the same location.

## EXAMPLE

The program below demonstrates the use of `pthread_setname_np()` and `pthread_getname_np()`.

The following shell session shows a sample run of the program:

```
$ ./a.out
```

```
Created a thread. Default name is: a.out
```

The thread name after setting it is THREADFOO.

```
^Z          # Suspend the program
```

```
[1]+ Stopped ./a.out
```

```
$ ps H -C a.out -o 'pid tid cmd comm'
```

PID	TID	CMD	COMMAND
5990	5990	./a.out	a.out
5990	5991	./a.out	THREADFOO

```
$ cat /proc/5990/task/5990/comm
```

```
a.out
```

```
$ cat /proc/5990/task/5991/comm
```

```
THREADFOO
```

Program source

```
#define _GNU_SOURCE
#include <pthread.h>
#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <errno.h>
#include <stdlib.h>
#define NAMELEN 16
#define errExitEN(en, msg) \
    do { errno = en; perror(msg); exit(EXIT_FAILURE); \
    } while (0)
static void *
threadfunc(void *parm)
{
    sleep(5);    // allow main program to set the thread name
    return NULL;
}
int
main(int argc, char **argv)
{
    pthread_t thread;
```

```

int rc;

char thread_name[NAMELEN];

rc = pthread_create(&thread, NULL, threadfunc, NULL);

if (rc != 0)
    errExitEN(rc, "pthread_create");

rc = pthread_getname_np(thread, thread_name, NAMELEN);

if (rc != 0)
    errExitEN(rc, "pthread_getname_np");

printf("Created a thread. Default name is: %s\n", thread_name);

rc = pthread_setname_np(thread, (argc > 1) ? argv[1] : "THREADFOO");

if (rc != 0)
    errExitEN(rc, "pthread_setname_np");

sleep(2);

rc = pthread_getname_np(thread, thread_name,
                        (argc > 2) ? atoi(argv[1]) : NAMELEN);

if (rc != 0)
    errExitEN(rc, "pthread_getname_np");

printf("The thread name after setting it is %s.\n", thread_name);

rc = pthread_join(thread, NULL);

if (rc != 0)
    errExitEN(rc, "pthread_join");

printf("Done\n");

exit(EXIT_SUCCESS);
}

```

## SEE ALSO

prctl(2), pthread\_create(3), pthreads(7)

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.