



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'radeon.4'***

**C:\>man radeon.4**

RADEON(4)                      Kernel Interfaces Manual                      RADEON(4)

### NAME

radeon - ATI/AMD RADEON video driver

### SYNOPSIS

Section "Device"

Identifier "devname"

Driver "radeon"

...

EndSection

### DESCRIPTION

radeon is an Xorg driver for ATI/AMD RADEON-based video cards with the following features:

? Full support for 8-, 15-, 16- and 24-bit pixel depths, and for 30-bit depth on

Linux 3.16 and later;

? RandR 1.2 and RandR 1.3 support;

? Full EXA 2D acceleration;

? Textured XVideo acceleration including anti-tearing support (Bicubic filtering only available on R/RV3xx, R/RV/RS4xx, R/RV5xx, and RS6xx/RS740);

? 3D acceleration;

### SUPPORTED HARDWARE

The radeon driver supports PCI, AGP, and PCIe video cards based on the following

ATI/AMD chips (note: list is non-exhaustive):

R100     Radeon 7200  
RV100    Radeon 7000(VE), M6, RN50/ES1000  
RS100    Radeon IGP320(M)  
RV200    Radeon 7500, M7, FireGL 7800  
RS200    Radeon IGP330(M)/IGP340(M)  
RS250    Radeon Mobility 7000 IGP  
R200     Radeon 8500, 9100, FireGL 8800/8700  
RV250    Radeon 9000PRO/9000, M9  
RV280    Radeon 9200PRO/9200/9200SE/9250, M9+  
RS300    Radeon 9100 IGP  
RS350    Radeon 9200 IGP  
RS400/RS480 Radeon XPRESS 200(M)/1100 IGP  
R300     Radeon 9700PRO/9700/9500PRO/9500/9600TX, FireGL X1/Z1  
R350     Radeon 9800PRO/9800SE/9800, FireGL X2  
R360     Radeon 9800XT  
RV350    Radeon 9600PRO/9600SE/9600/9550, M10/M11, FireGL T2  
RV360    Radeon 9600XT  
RV370    Radeon X300, M22  
RV380    Radeon X600, M24  
RV410    Radeon X700, M26 PCIe  
R420     Radeon X800 AGP  
R423/R430 Radeon X800, M28 PCIe  
R480/R481 Radeon X850 PCIe/AGP  
RV505/RV515/RV516/RV550  
          Radeon X1300/X1400/X1500/X1550/X2300  
R520     Radeon X1800  
RV530/RV560 Radeon X1600/X1650/X1700  
RV570/R580 Radeon X1900/X1950  
RS600/RS690/RS740  
          Radeon X1200/X1250/X2100  
R600     Radeon HD 2900  
RV610/RV630 Radeon HD 2400/2600/2700/4200/4225/4250  
RV620/RV635 Radeon HD 3410/3430/3450/3470/3650/3670

RV670 Radeon HD 3690/3850/3870

RS780/RS880 Radeon HD 3100/3200/3300/4100/4200/4250/4290

RV710/RV730 Radeon HD 4330/4350/4550/4650/4670/5145/5165/530v/545v/560v/565v

RV740/RV770/RV790

Radeon HD 4770/4730/4830/4850/4860/4870/4890

CEDAR Radeon HD 5430/5450/6330/6350/6370

REDWOOD Radeon HD 5550/5570/5650/5670/5730/5750/5770/6530/6550/6570

JUNIPER Radeon HD 5750/5770/5830/5850/5870/6750/6770/6830/6850/6870

CYPRESS Radeon HD 5830/5850/5870

HEMLOCK Radeon HD 5970

PALM Radeon HD 6310/6250

SUMO/SUMO2 Radeon HD 6370/6380/6410/6480/6520/6530/6550/6620

BARTS Radeon HD 6790/6850/6870/6950/6970/6990

TURKS Radeon HD 6570/6630/6650/6670/6730/6750/6770

CAICOS Radeon HD 6430/6450/6470/6490

CAYMAN Radeon HD 6950/6970/6990

ARUBA Radeon HD 7000 series

TAHITI Radeon HD 7900 series

PITCAIRN Radeon HD 7800 series

VERDE Radeon HD 7700 series

OLAND Radeon HD 8000 series

HAINAN Radeon HD 8000 series

BONAIRE Radeon HD 7790 series

KAVERI KAVERI APUs

KABINI KABINI APUs

HAWAII Radeon R9 series

MULLINS MULLINS APUs

## CONFIGURATION DETAILS

Please refer to `xorg.conf(5)` for general configuration details. This section only covers configuration details specific to this driver.

The following driver Options are supported:

Option "SWcursor" "boolean"

Selects software cursor. The default is off.

#### Option "Accel" "boolean"

Enables or disables all hardware acceleration.

The default is on.

#### Option "ZaphodHeads" "string"

Specify the RandR output(s) to use with zaphod mode for a particular driver instance. If you use this option you must use this option for all instances of the driver.

For example: Option "ZaphodHeads" "LVDS,VGA-0" will assign xrandr outputs LVDS and VGA-0 to this instance of the driver.

#### Option "ColorTiling" "boolean"

The framebuffer can be addressed either in linear or tiled mode. Tiled mode can provide significant performance benefits with 3D applications. Tiling will be disabled if the drm module is too old or if the current display configuration does not support it. On R600+ this enables 1D tiling mode.

The default value is on for R/RV3XX, R/RV4XX, R/RV5XX, RS6XX, RS740, R/RV6XX, R/RV7XX, RS780, RS880, EVERGREEN, CAYMAN, ARUBA, Southern Islands, and Sea Islands and off for R/RV/RS1XX, R/RV/RS2XX, RS3XX, and RS690/RS780/RS880 when fast fb feature is enabled.

#### Option "ColorTiling2D" "boolean"

The framebuffer can be addressed either in linear, 1D, or 2D tiled modes. 2D tiled mode can provide significant performance benefits over 1D tiling with 3D applications. Tiling will be disabled if the drm module is too old or if the current display configuration does not support it. KMS ColorTiling2D is only supported on R600 and newer chips and requires Mesa 9.0 or newer for R6xx-ARUBA, Mesa 9.2 or newer for Southern Islands, and Mesa 10.1 or newer for Sea Islands.

The default value is on for R/RV6XX, R/RV7XX, RS780, RS880, EVERGREEN, CAYMAN, ARUBA, Southern Islands, and Sea Islands.

#### Option "DRI" "integer"

Define the maximum level of DRI to enable. Valid values are 2 for DRI2 or 3 for DRI3. The default is 3 for DRI3 if the Xorg version is  $\geq$  1.18.3 and glamor is enabled, otherwise 2 for DRI2. Note: DRI3 may not work correctly in all cases with EXA, enable at your own risk.

Option "EnablePageFlip" "boolean"

Enable DRI2 page flipping. The default is on. Pageflipping is supported on all radeon hardware.

Option "TearFree" "boolean"

Set the default value of the per-output 'TearFree' property, which controls tearing prevention using the hardware page flipping mechanism. TearFree is on for any CRTC associated with one or more outputs with TearFree on. Two separate scanout buffers need to be allocated for each CRTC with TearFree on. If this option is set, the default value of the property is 'on' or 'off' accordingly. If this option isn't set, the default value of the property is auto, which means that TearFree is on for rotated outputs, outputs with RandR transforms applied and for RandR 1.4 slave outputs, otherwise off.

Option "AccelMethod" "string"

Chooses between available acceleration architectures. Valid values are EXA (for pre-TAHITI GPUs) and glamor (for R300 or higher). The default is glamor with R600 or newer (with Xorg >= 1.18.3, otherwise with TAHITI or newer), otherwise EXA.

The following driver Options are supported for glamor :

Option "ShadowPrimary" "boolean"

This option enables a so-called "shadow primary" buffer for fast CPU access to pixel data, and separate scanout buffers for each display controller (CRTC). This may improve performance for some 2D workloads, potentially at the expense of other (e.g. 3D, video) workloads. Note in particular that enabling this option currently disables page flipping. The default is off.

The following driver Options are supported for EXA :

Option "EXAVSync" "boolean"

This option attempts to avoid tearing by stalling the engine until the display controller has passed the destination region. It reduces tearing at the cost of performance and has been known to cause instability on some chips. The default is off.

Option "EXAPixmaps" "boolean"

Under KMS, to avoid thrashing pixmaps in/out of VRAM on low memory cards, we

use a heuristic based on VRAM amount to determine whether to allow EXA to use VRAM for non-essential pixmaps. This option allows us to override the heuristic. The default is on with > 32MB VRAM, off with < 32MB or when fast fb feature is enabled for RS690/RS780/RS880.

Option "SwapbuffersWait" "boolean"

This option controls the behavior of glXSwapBuffers and glXCopySubBufferMESA calls by GL applications. If enabled, the calls will avoid tearing by making sure the display scanline is outside of the area to be copied before the copy occurs. If disabled, no scanline synchronization is performed, meaning tearing will likely occur. Note that when enabled, this option can adversely affect the framerate of applications that render frames at less than refresh rate.

The default value is on.

## TEXTURED VIDEO ATTRIBUTES

The driver supports the following X11 Xv attributes for Textured Video. You can use the "xvattr" tool to query/set those attributes at runtime.

### XV\_VSYNC

XV\_VSYNC is used to control whether textured adapter synchronizes the screen update to the monitor vertical refresh to eliminate tearing. It has two values: 'off'(0) and 'on'(1). The default is 'on'(1).

### XV\_CRTC

XV\_CRTC is used to control which display controller (crtc) the textured adapter synchronizes the screen update with when XV\_VSYNC is enabled. The default, 'auto'(-1), will sync to the display controller that more of the video is on; when this is ambiguous, the display controller associated with the RandR primary output is preferred. This attribute is useful for things like clone mode where the user can best decide which display should be synced. The default is 'auto'(-1).

### XV\_BICUBIC

XV\_BICUBIC is used to control whether textured adapter should apply a bicubic filter to smooth the output. It has three values: 'off'(0), 'on'(1) and 'auto'(2). 'off' means never apply the filter, 'on' means always apply the filter and 'auto' means apply the filter only if the X and Y sizes are

scaled to more than double to avoid blurred output. Bicubic filtering is not currently compatible with other Xv attributes like hue, contrast, and brightness, and must be disabled to use those attributes. The default is 'off'(0).

## SEE ALSO

Xorg(1), xorg.conf(5), Xserver(1), X(7)

1. Wiki page:

<https://www.x.org/wiki/radeon>

2. Overview about radeon development code:

<https://cgit.freedesktop.org/xorg/driver/xf86-video-ati/>

3. Mailing list:

<https://lists.freedesktop.org/mailman/listinfo/amd-gfx>

4. IRC channel:

#radeon on irc.freenode.net

5. Query the bugtracker for radeon bugs:

<https://bugs.freedesktop.org/query.cgi?product=xorg&component=Driver/Radeon>

6. Submit bugs & patches:

[https://bugs.freedesktop.org/enter\\_bug.cgi?product=xorg&component=Driver/Radeon](https://bugs.freedesktop.org/enter_bug.cgi?product=xorg&component=Driver/Radeon)

## AUTHORS

Authors include:

Rickard E. (Rik) Faith [faith@precisioninsight.com](mailto:faith@precisioninsight.com)

Kevin E. Martin [kem@freedesktop.org](mailto:kem@freedesktop.org)

Alan Hourihane [alanh@fairlite.demon.co.uk](mailto:alanh@fairlite.demon.co.uk)

Marc Aurele La France [tsi@xfree86.org](mailto:tsi@xfree86.org)

Benjamin Herrenschmidt [benh@kernel.crashing.org](mailto:benh@kernel.crashing.org)

Michel D?nzer [michel@daenzer.net](mailto:michel@daenzer.net)

Alex Deucher [alexdeucher@gmail.com](mailto:alexdeucher@gmail.com)

Bogdan D. [bogdand@users.sourceforge.net](mailto:bogdand@users.sourceforge.net)

Eric Anholt [eric@anholt.net](mailto:eric@anholt.net)

X Version 11

xf86-video-ati 19.1.0

RADEON(4)