



Rocky Enterprise Linux 9.2 Manual Pages on command 'rdma-link.8'

C:\>man rdma-link.8

RDMA-LINK(8) Linux RDMA-LINK(8)

NAME

rdma-link - rdma link configuration

SYNOPSIS

devlink [OPTIONS] link { COMMAND | help }

OPTIONS := { -V[ersion] | -d[etails] }

rdma link show [DEV/PORT_INDEX]

rdma link add NAME type TYPE netdev NETDEV

rdma link delete NAME

rdma link help

DESCRIPTION

rdma link show - display rdma link attributes

DEV/PORT_INDEX - specifies the RDMA link to show. If this argument is omitted all links are listed.

rdma link add NAME type TYPE netdev NETDEV - add an rdma link for the specified type to the network device

NAME - specifies the new name of the rdma link to add

TYPE - specifies which rdma type to use. Link types:

 rx - Soft RoCE driver

 siw - Soft iWARP driver

NETDEV - specifies the network device to which the link is bound

rdma link delete NAME - delete an rdma link

NAME - specifies the name of the rdma link to delete

EXAMPLES

```
rdma link show
```

Shows the state of all rdma links on the system.

```
rdma link show mlx5_2/1
```

Shows the state of specified rdma link.

```
rdma link add rxe_eth0 type rxe netdev eth0
```

Adds a RXE link named rxe_eth0 to network device eth0

```
rdma link del rxe_eth0
```

Removes RXE link rxe_eth0

SEE ALSO

rdma(8), rdma-dev(8), rdma-resource(8), rdma-statistic(8),

AUTHOR

Leon Romanovsky <leonro@mellanox.com>

iproute2

06 Jul 2017

RDMA-LINK(8)