



Rocky Enterprise Linux 9.2 Manual Pages on command 'readlink.1'

C:\>man readlink.1

READLINK(1) User Commands READLINK(1)

NAME

readlink - print resolved symbolic links or canonical file names

SYNOPSIS

readlink [OPTION]... FILE...

DESCRIPTION

Note `realpath(1)` is the preferred command to use for canonicalization functional?

ity.

Print value of a symbolic link or canonical file name

`-f, --canonicalize`

canonicalize by following every symlink in every component of the given name recursively; all but the last component must exist

`-e, --canonicalize-existing`

canonicalize by following every symlink in every component of the given name recursively, all components must exist

`-m, --canonicalize-missing`

canonicalize by following every symlink in every component of the given name recursively, without requirements on components existence

`-n, --no-newline`

do not output the trailing delimiter

`-q, --quiet`

`-s, --silent`

suppress most error messages (on by default)

`-v, --verbose`

report error messages

`-z, --zero`

end each output line with NUL, not newline

`--help` display this help and exit

`--version`

output version information and exit

AUTHOR

Written by Dmitry V. Levin.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report readlink translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

`readlink(2)`, `realpath(1)`, `realpath(3)`

Full documentation at: <<https://www.gnu.org/software/coreutils/readlink>>

or available locally via: `info '(coreutils) readlink invocation'`

GNU coreutils 8.30

September 2019

READLINK(1)