



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'rpc.5'***

**C:\>man rpc.5**

RPC(5)                      Linux Programmer's Manual                      RPC(5)

### NAME

rpc - RPC program number data base

### SYNOPSIS

/etc/rpc

### DESCRIPTION

The `rpc` file contains user readable names that can be used in place of RPC program numbers. Each line has the following information:

- ? name of server for the RPC program
- ? RPC program number
- ? aliases

Items are separated by any number of blanks and/or tab characters. A '#' indicates the beginning of a comment; characters from the '#' to the end of the line are not interpreted by routines which search the file.

Here is an example of the `/etc/rpc` file from the Sun RPC Source distribution.

```
#
# rpc 88/08/01 4.0 RPCSRC; from 1.12 88/02/07 SMI
#
portmapper    100000  portmap sunrpc
rstatd        100001  rstat rstat_svc rup perfmeter
rusersd       100002  rusers
nfs           100003  nfsprog
```

ypserv	100004	ypprog
mountd	100005	mount showmount
ypbind	100007	
walld	100008	rwall shutdown
yppasswdd	100009	yppasswd
etherstatd	100010	etherstat
rquotad	100011	rquotaprog quota rquota
sprayd	100012	spray
3270_mapper	100013	
rje_mapper	100014	
selection_svc	100015	selnsvc
database_svc	100016	
rex	100017	rex
alis	100018	
sched	100019	
llockmgr	100020	
nlockmgr	100021	
x25.inr	100022	
statmon	100023	
status	100024	
bootparam	100026	
ypupdated	100028	ypupdate
keyserv	100029	keyserver
tfsd	100037	
nseed	100038	
nsemntd	100039	

## FILES

/etc/rpc

RPC program number data base

## SEE ALSO

getrpcent(3)

## COLOPHON

the project, information about reporting bugs, and the latest version of this page,  
can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

RPC(5)