



Rocky Enterprise Linux 9.2 Manual Pages on command 'rpmdb.8'

C:\>man rpmdb.8

RPMDDB(8) System Manager's Manual RPMDDB(8)

NAME

rpmdb - RPM Database Tool

SYNOPSIS

rpm {--initdb|--rebuilddb}

DESCRIPTION

The general form of an rpm rebuild database command is

rpm {--initdb|--rebuilddb} [-v] [--dbpath DIRECTORY] [--root DIRECTORY]

Use --initdb to create a new database if one doesn't already exist (existing data? base is not overwritten), use --rebuilddb to rebuild the database indices from the installed package headers.

SEE ALSO

popt(3),

rpm(8),

rpmkeys(8),

rpmsign(8),

rpm2cpio(8),

rpmbuild(8),

rpmspec(8),

rpm --help - as rpm supports customizing the options via popt aliases it's impossi?

ble to guarantee that what's described in the manual matches what's available.

<http://www.rpm.org/> <URL:<http://www.rpm.org/>>

AUTHORS

Marc Ewing <marc@redhat.com>

Jeff Johnson <jbj@redhat.com>

Erik Troan <ewt@redhat.com>

Panu Matilainen <pmatilai@redhat.com>

Red Hat, Inc

29 June 2010

RPMDDB(8)