



Rocky Enterprise Linux 9.2 Manual Pages on command 'rygel.1'

C:\>man rygel.1

RYGEL(1) Rygel User Manual RYGEL(1)

NAME

rygel - a collection of DLNA/UPnP AV services

SYNOPSIS

rygel [options]

DESCRIPTION

rygel is a home media solution that allows you to easily share audio, video and pictures, and control of media player on your home network. In technical terms it is both a UPnP AV MediaServer and MediaRenderer implemented through a plug-in mechanism. Interoperability with other devices in the market is achieved by conformance to very strict requirements of DLNA and on the fly conversion of media to format that client devices are capable of handling.

OPTIONS

The program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

-h, --help

Show summary of options.

--version

Show version of program.

-n, --network-interface=INTERFACE

Set the network interfaces rygel listens on. Can be used multiple times for to configure multiple interfaces. INTERFACE can be an IP, a device name or an

ESSID (Linux only).

-p, --port=PORT
Set the listen-port.

-t, --disable-transcoding
Disable any transcoding.

-U, --disallow-upload
Disable uploading of media files via UPnP.

-D, --disallow-deletion
UPnP clients are not allowed to delete media files on the server.

-g, --log-level=LEVEL
Comma-separated list of DOMAIN:LEVEL pairs, allowing to set the log level individually for each domain, where DOMAIN is either "*", "rygel" or the name of a plugin. Allowed log levels are 1=critical, 2=error, 3=warning, 4=message/info, 5=debug.

-u, --plugin-path=PATH
Set the plugin search path.

-e, --engine-path=ENGINE_PATH
Set the media streaming and transcoding engine search path.

-d, --disable-plugin=PLUGIN_NAME
Disable the plugin PLUGIN_NAME.

-i, --title=PLUGIN_NAME:TITLE
Set the title of plugin PLUGIN_NAME to TITLE You can use this option more than once for every plugin you want to set the name of.

-o, --plugin-option=PLUGIN_NAME: OPTION:VALUE1[,VALUE2,...]
Set options for a plugin.

-P, --disable-upnp
Disable advertisement via UPnP and set rygel into streaming-only mode.

-c, --config=CONFIG_FILE
Use CONFIG_FILE instead of \${XDG_CONFIG_DIR}/rygel.conf.

-s, --shutdown
Shutdown a currently running instance of rygel

-r, --replace
Replace the currently running instance of rygel with this instance. Short for

```
rygel -s && rygel
```

FILES

/etc/rygel.conf

The system-wide configuration file to control the behaviour of rygel. See rygel.conf(5) for further details.

`\${XDG_CONFIG_DIR}/rygel.conf

The per-user configuration file to control the behaviour of rygel. See rygel.conf(5) for further details.

`\${XDG_CONFIG_DIR}/Rygel/*.xml

Cached UPnP device description files.

ENVIRONMENT

RYGEL_DISABLE_UPNP

Disable advertisement via UPnP and set rygel into streaming-only mode.

RYGEL_IFACE

Set the network interfaces to bind to.

RYGEL_PORT

Define the network port to bind to.

RYGEL_DISABLE_TRANSCODING

Disable transcoding globally.

RYGEL_LOG

Set the log level of rygel.

RYGEL_PLUGIN_PATH

Set the plugin search path of rygel.

RYGEL_ENGINE_PATH

Set the media streaming and transcoding engine search path for rygel.

RYGEL_MEDIA_ENGINE

Set a specific media streaming engine to pick up from the media engine search path.

RYGEL_DISABLE_UPLOAD

Disable media file upload via UPnP.

RYGEL_DISABLE_DELETION

Disable remote file deletion via UPnP.

RYGEL_PLUGIN_TIMEOUT

Set the time-out for finding the plugins. Useful to increase when running inside valgrind.

RYGEL_DATABASE_DEBUG

If set to 1, the database library will print the used SQL statements.

Also for every plugin you can set the following environment variables:

RYGEL_PLUGIN_NAME_TITLE

Set the title of the plugin.

RYGEL_PLUGIN_NAME_ENABLED

Enable or disable the plugin.

BUGS

The BTS can be found at <https://gitlab.gnome.org/GNOME/rygel/issues>.

SEE ALSO

`rygel.conf(5)`

AUTHOR

Jens Georg <mail@jensge.org>

Wrote this manpage.

rygel

11/23/2019

RYGEL(1)