



Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-escl.5'

C:\>man sane-escl.5

sane-escl(5) SANE Scanner Access Now Easy sane-escl(5)

NAME

sane-escl - SANE backend for eSCL scanners

DESCRIPTION

The sane-escl library implements a SANE (Scanner Access Now Easy) backend that provides access to eSCL protocol scanners.

The "escl" backend for SANE supports AirScan/eSCL devices that announce themselves on mDNS as `_uscan._utcp` or `_uscans._utcp`. If the device is available, the "escl" backend recovers these capacities. The user configures and starts scanning. A list of devices that use the eSCL protocol can be found at <https://support.apple.com/en-us/HT201311>. While these devices are expected to work, your mileage may vary.

FILES

@CONFIGDIR@/escl.conf

The backend configuration file.

@LIBDIR@/libsane-escl.a

The static library implementing this backend.

@LIBDIR@/libsane-escl.so

The shared library implementing this backend (present on systems that support dynamic loading).

ENVIRONMENT

SANE_DEBUG_ESCL

If the library was compiled with debug support enabled, this environment variable controls the debug level for this backend. E.g., a value of 128 requests all debug output to be printed. Smaller levels reduce verbosity.

SEE ALSO

sane(7), scanimage(1), xscanimage(1), xsane(1)

AUTHORS

Touboul Nathane, Thierry HUCHARD

@PACKAGEVERSION@

14 Dec 2019

sane-escl(5)