



Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-gphoto2.5'

C:\>man sane-gphoto2.5

sane-gphoto2(5) SANE Scanner Access Now Easy sane-gphoto2(5)

NAME

sane-gphoto2 - SANE backend for gphoto2 supported cameras

DESCRIPTION

The sane-gphoto2 library implements a SANE (Scanner Access Now Easy) backend that provides access to the digital cameras supported by gphoto2. This backend has only been tested with a handful of cameras so far. Patches to support other models are welcome.

Because of the limited testing of this backend, it is commented out in @CON? FIGDIR@/dll.conf by default. Either the comment character must be removed or the backend must be called explicitly. E.g. `scanimage -d gphoto2' or `xscanimage gphoto2'.

DEVICE NAMES

The current version of the backend only allows one camera to be connected. The device name is always "0".

CONFIGURATION

The contents of the gphoto2.conf specify the characteristics of the camera to be used. Resolutions (high resolution, low resolution, and thumbnail size) are required since they are needed by the sane frontends, but can't be obtained through the gphoto2 interface. Valid ports and cameras can be obtained by "gphoto2 --list-cameras" and "gphoto2 --list-ports".

The dumpinquiry line causes some information about the camera to be printed.

Empty lines and lines starting with a hash mark (#) are ignored. A sample configuration file is shown below:

The "topfolder" line specifies the "fixed" part of the file path. For example, on the Kodak DC-240, files are stored in the directory /DCIM/100DC240. The /DCIM portion is constant, but 100DC240 will change and must be read from the camera. In this case, the line would read "topfolder=/DCIM"

Some cameras don't implement a file structure and store all pictures in the root directory. This is indicated by setting "subdirs=0" with "topfolder=/"

```
port=usb:
camera=Kodak DC240
# this is a comment
high_resolution=1280x960
low_resolution=640x480
thumb_resolution=160x120
dumpinquiry
```

FILES

@CONFIGDIR@gphoto2.conf

The backend configuration file (see also description of SANE_CONFIG_DIR below).

@LIBDIR@/libsane-gphoto2.a

The static library implementing this backend.

@LIBDIR@/libsane-gphoto2.so

The shared library implementing this backend (present on systems that support dynamic loading).

ENVIRONMENT

SANE_CONFIG_DIR

This environment variable specifies the list of directories that may contain the configuration file. Under UNIX, the directories are separated by a colon (:), under OS/2, they are separated by a semi-colon (;). If this variable is not set, the configuration file is searched in two default directories: first, the current working directory (".") and then in @CONFIGDIR@. If the value of the environment variable ends with the directory separator character, then the default directories are searched after the ex-

plicitly specified directories. For example, setting SANE_CONFIG_DIR to "/tmp/config:" would result in directories "tmp/config", ".", and "@CONFIGDIR@" being searched (in this order).

SANE_DEBUG_GPHOTO2

If the library was compiled with debugging support enabled, this environment variable controls the debug level for this backend. A value of 128 requests maximally copious debug output; smaller levels reduce verbosity.

GP_DEBUG

Set to 1, 2, or 3, to enable various levels of debugging within the gphoto2 libraries.

SEE ALSO

sane(7)

AUTHOR

Peter S. Fales

The manpage was largely copied from the dc210 manpage.

BUGS

Many, no doubt.

More general comments, suggestions, and inquiries about frontends or SANE should go to the SANE Developers mailing list (see <http://www.sane-project.org/missing-lists.html> for details). You must be subscribed to the list, otherwise your mail won't be sent to the subscribers.

@PACKAGEVERSION@

11 Jul 2008

sane-gphoto2(5)