



Rocky Enterprise Linux 9.2 Manual Pages on command 'select-default-ispell.8'

C:\>man select-default-ispell.8

SELECT-DEFAULT-ISPELL(8)

SELECT-DEFAULT-ISPELL(8)

NAME

select-default-ispell - select default ispell dictionary

SYNOPSIS

select-default-ispell [options]

Options (all long only options):

- set-default='regexp' Try 'regexp' to get a single match and set it as default. Fail otherwise.
- show-choices Show available choices to STDERR and exit.
- debug Enable debug mode

DESCRIPTION

This program is responsible for selecting default ispell dictionary.

If --show-choices is used will just output a list of available choices to STDERR and exit. STDOUT cannot be used, this program loads debconf and debconf captures STDOUT.

If --set-default is used, program will try to get a single regexp match from

available choices, failing if not. Will try case dependent match first, then case independent.

If `--set-default` is not used this program will make `debconf` always ask the shared question about the default `ispell` dictionary to be used in your system according to the installed ones.

In both cases, will do the appropriate settings if needed.

Calls internally `update-default-ispell`.

SEE ALSO

The `dictionaries-common` policy document

AUTHORS

Rafael Laboissiere, Agustin Martin

1.28.1 2018-11-15 `SELECT-DEFAULT-ISPELL(8)`