



Rocky Enterprise Linux 9.2 Manual Pages on command 'select-default-wordlist.8'

C:\>man select-default-wordlist.8

SELECT-DEFAULT-WORDLIST(8)

SELECT-DEFAULT-WORDLIST(8)

NAME

select-default-wordlist - select default wordlist

SYNOPSIS

select-default-wordlist [options]

Options (all long only options):

--set-default='regexp' Try 'regexp' to get a single match and set

it as default. Fail otherwise.

--show-choices Show available choices to STDERR and exit.

--debug Enable debug mode

DESCRIPTION

This program is responsible for selecting default wordlist.

If --show-choices is used will just output a list of available choices to STDERR and exit. STDOUT cannot be used, this program loads debconf and debconf captures STDOUT.

If --set-default is used, program will try to get a single regexp match from

available choices, failing if not. Will try case dependent match first, then case independent.

If `--set-default` is not used this program will make `debconf` always ask the shared question about the default wordlist to be used in your system according to the installed ones.

In both cases, will do the appropriate settings if needed.

Calls internally `update-default-wordlist`.

SEE ALSO

The `dictionaries-common` policy document

AUTHORS

Rafael Laboissiere, Agustin Martin

1.28.1 2018-11-15 `SELECT-DEFAULT-WORDLIST(8)`