



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'seteuid.2'***

**C:\>man seteuid.2**

SETEUID(2)                   Linux Programmer's Manual                   SETEUID(2)

### NAME

seteuid, setegid - set effective user or group ID

### SYNOPSIS

```
#include <sys/types.h>
```

```
#include <unistd.h>
```

```
int seteuid(uid_t euid);
```

```
int setegid(gid_t egid);
```

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

```
seteuid(), setegid():
```

```
  _POSIX_C_SOURCE >= 200112L
```

```
  || /* Glibc versions <= 2.19: */ _BSD_SOURCE
```

### DESCRIPTION

`seteuid()` sets the effective user ID of the calling process. Unprivileged processes may only set the effective user ID to the real user ID, the effective user ID or the saved set-user-ID.

Precisely the same holds for `setegid()` with "group" instead of "user".

### RETURN VALUE

On success, zero is returned. On error, -1 is returned, and `errno` is set appropriately.

Note: there are cases where `seteuid()` can fail even when the caller is UID 0; it is a grave security error to omit checking for a failure return from `seteuid()`.

## ERRORS

**EINVAL** The target user or group ID is not valid in this user namespace.

**EPERM** In the case of `seteuid()`: the calling process is not privileged (does not have the `CAP_SETUID` capability in its user namespace) and `euid` does not match the current real user ID, current effective user ID, or current saved `set-user-ID`.

In the case of `setegid()`: the calling process is not privileged (does not have the `CAP_SETGID` capability in its user namespace) and `egid` does not match the current real group ID, current effective group ID, or current saved `set-group-ID`.

## CONFORMING TO

POSIX.1-2001, POSIX.1-2008, 4.3BSD.

## NOTES

Setting the effective user (group) ID to the saved `set-user-ID` (saved `set-group-ID`) is possible since Linux 1.1.37 (1.1.38). On an arbitrary system one should check `_POSIX_SAVED_IDS`.

Under `glibc 2.0`, `seteuid(euid)` is equivalent to `setreuid(-1, euid)` and hence may change the saved `set-user-ID`. Under `glibc 2.1` and later, it is equivalent to `setresuid(-1, euid, -1)` and hence does not change the saved `set-user-ID`. Analogous remarks hold for `setegid()`, with the difference that the change in implementation from `setregid(-1, egid)` to `setresgid(-1, egid, -1)` occurred in `glibc 2.2` or `2.3` (depending on the hardware architecture).

According to POSIX.1, `seteuid()` (`setegid()`) need not permit `euid` (`egid`) to be the same value as the current effective user (group) ID, and some implementations do not permit this.

## C library/kernel differences

On Linux, `seteuid()` and `setegid()` are implemented as library functions that call, respectively, `setreuid(2)` and `setregid(2)`.

## SEE ALSO

`geteuid(2)`, `setresuid(2)`, `setreuid(2)`, `setuid(2)`, `capabilities(7)`, `credentials(7)`, `user_namespaces(7)`

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of

the project, information about reporting bugs, and the latest version of this page,  
can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2017-09-15

SETEUID(2)