



Rocky Enterprise Linux 9.2 Manual Pages on command 'sprof.1'

C:\>man sprof.1

SPROF(1)

Linux User Manual

SPROF(1)

NAME

sprof - read and display shared object profiling data

SYNOPSIS

sprof [option]... shared-object-path [profile-data-path]

DESCRIPTION

The `sprof` command displays a profiling summary for the shared object (shared library) specified as its first command-line argument. The profiling summary is created using previously generated profiling data in the (optional) second command-line argument. If the profiling data pathname is omitted, then `sprof` will attempt to deduce it using the soname of the shared object, looking for a file with the name `<soname>.profile` in the current directory.

OPTIONS

The following command-line options specify the profile output to be produced:

`-c, --call-pairs`

Print a list of pairs of call paths for the interfaces exported by the shared object, along with the number of times each path is used.

`-p, --flat-profile`

Generate a flat profile of all of the functions in the monitored object, with counts and ticks.

`-q, --graph`

Generate a call graph.

If none of the above options is specified, then the default behavior is to display a flat profile and a call graph.

The following additional command-line options are available:

-?, --help

Display a summary of command-line options and arguments and exit.

--usage

Display a short usage message and exit.

-V, --version

Display the program version and exit.

CONFORMING TO

The `sprof` command is a GNU extension, not present in POSIX.1.

EXAMPLE

The following example demonstrates the use of `sprof`. The example consists of a main program that calls two functions in a shared object. First, the code of the main program:

```
$ cat prog.c
#include <stdlib.h>

void x1(void);
void x2(void);

int
main(int argc, char *argv[])
{
    x1();
    x2();
    exit(EXIT_SUCCESS);
}
```

The functions `x1()` and `x2()` are defined in the following source file that is used to construct the shared object:

```
$ cat libdemo.c
#include <unistd.h>

void
consumeCpu1(int lim)
{
```

```

int j;
for (j = 0; j < lim; j++)
    getppid();
}
void
x1(void) {
    int j;
    for (j = 0; j < 100; j++)
        consumeCpu1(200000);
}
void
consumeCpu2(int lim)
{
    int j;
    for (j = 0; j < lim; j++)
        getppid();
}
void
x2(void)
{
    int j;
    for (j = 0; j < 1000; j++)
        consumeCpu2(10000);
}

```

Now we construct the shared object with the real name libdemo.so.1.0.1, and the soname libdemo.so.1:

```

$ cc -g -fPIC -shared -Wl,-soname,libdemo.so.1 \
    -o libdemo.so.1.0.1 libdemo.c

```

Then we construct symbolic links for the library soname and the library linker name:

```

$ ln -sf libdemo.so.1.0.1 libdemo.so.1
$ ln -sf libdemo.so.1 libdemo.so

```

Next, we compile the main program, linking it against the shared object, and then

list the dynamic dependencies of the program:

```
$ cc -g -o prog prog.c -L. -ldemo
$ ldd prog
linux-vdso.so.1 => (0x00007fff86d66000)
libdemo.so.1 => not found
libc.so.6 => /lib64/libc.so.6 (0x00007fd4dc138000)
/lib64/ld-linux-x86-64.so.2 (0x00007fd4dc51f000)
```

In order to get profiling information for the shared object, we define the environ?

ment variable LD_PROFILE with the soname of the library:

```
$ export LD_PROFILE=libdemo.so.1
```

We then define the environment variable LD_PROFILE_OUTPUT with the pathname of the

directory where profile output should be written, and create that directory if it

does not exist already:

```
$ export LD_PROFILE_OUTPUT=$(pwd)/prof_data
$ mkdir -p $LD_PROFILE_OUTPUT
```

LD_PROFILE causes profiling output to be appended to the output file if it already

exists, so we ensure that there is no preexisting profiling data:

```
$ rm -f $LD_PROFILE_OUTPUT/$LD_PROFILE.profile
```

We then run the program to produce the profiling output, which is written to a file

in the directory specified in LD_PROFILE_OUTPUT:

```
$ LD_LIBRARY_PATH=. ./prog
$ ls prof_data
libdemo.so.1.profile
```

We then use the sprprof -p option to generate a flat profile with counts and ticks:

```
$ sprprof -p libdemo.so.1 $LD_PROFILE_OUTPUT/libdemo.so.1.profile
```

Flat profile:

Each sample counts as 0.01 seconds.

%	cumulative	self	self	total		
time	seconds	seconds	calls	us/call	us/call	name
60.00	0.06	0.06	100	600.00		consumeCpu1
40.00	0.10	0.04	1000	40.00		consumeCpu2
0.00	0.10	0.00	1	0.00	x1	
0.00	0.10	0.00	1	0.00	x2	

The `sprof -q` option generates a call graph:

```
$ sprof -q libdemo.so.1 $LD_PROFILE_OUTPUT/libdemo.so.1.profile
```

```
index % time  self children  called  name
      0.00  0.00  100/100    x1 [1]
[0] 100.0  0.00  0.00   100   consumeCpu1 [0]
-----
      0.00  0.00   1/1     <UNKNOWN>
[1]  0.0  0.00  0.00    1    x1 [1]
      0.00  0.00  100/100   consumeCpu1 [0]
-----
      0.00  0.00 1000/1000    x2 [3]
[2]  0.0  0.00  0.00  1000   consumeCpu2 [2]
-----
      0.00  0.00   1/1     <UNKNOWN>
[3]  0.0  0.00  0.00    1    x2 [3]
      0.00  0.00 1000/1000   consumeCpu2 [2]
-----
```

Above and below, the "<UNKNOWN>" strings represent identifiers that are outside of the profiled object (in this example, these are instances of `main()`).

The `sprof -c` option generates a list of call pairs and the number of their occurrences:

ences:

```
$ sprof -c libdemo.so.1 $LD_PROFILE_OUTPUT/libdemo.so.1.profile
```

```
<UNKNOWN>          x1          1
x1                 consumeCpu1    100
<UNKNOWN>          x2          1
x2                 consumeCpu2   1000
```

SEE ALSO

`gprof(1)`, `ldd(1)`, `ld.so(8)`

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.