



Rocky Enterprise Linux 9.2 Manual Pages on command 'stat.1'

C:\>man stat.1

STAT(1) User Commands STAT(1)

NAME

stat - display file or file system status

SYNOPSIS

stat [OPTION]... FILE...

DESCRIPTION

Display file or file system status.

Mandatory arguments to long options are mandatory for short options too.

-L, --dereference

follow links

-f, --file-system

display file system status instead of file status

-c --format=FORMAT

use the specified FORMAT instead of the default; output a newline after each use of FORMAT

--printf=FORMAT

like --format, but interpret backslash escapes, and do not output a mandatory trailing newline; if you want a newline, include \n in FORMAT

-t, --terse

print the information in terse form

--help display this help and exit

--version

output version information and exit

The valid format sequences for files (without --file-system):

- %a access rights in octal (note '#' and '0' printf flags)
- %A access rights in human readable form
- %b number of blocks allocated (see %B)
- %B the size in bytes of each block reported by %b
- %C SELinux security context string
- %d device number in decimal
- %D device number in hex
- %f raw mode in hex
- %F file type
- %g group ID of owner
- %G group name of owner
- %h number of hard links
- %i inode number
- %m mount point
- %n file name
- %N quoted file name with dereference if symbolic link
- %o optimal I/O transfer size hint
- %s total size, in bytes
- %t major device type in hex, for character/block device special files
- %T minor device type in hex, for character/block device special files
- %u user ID of owner
- %U user name of owner
- %w time of file birth, human-readable; - if unknown
- %W time of file birth, seconds since Epoch; 0 if unknown
- %x time of last access, human-readable
- %X time of last access, seconds since Epoch
- %y time of last data modification, human-readable
- %Y time of last data modification, seconds since Epoch
- %z time of last status change, human-readable
- %Z time of last status change, seconds since Epoch

Valid format sequences for file systems:

%a free blocks available to non-superuser
%b total data blocks in file system
%c total file nodes in file system
%d free file nodes in file system
%f free blocks in file system
%i file system ID in hex
%l maximum length of filenames
%n file name
%s block size (for faster transfers)
%S fundamental block size (for block counts)
%t file system type in hex
%T file system type in human readable form

--terse is equivalent to the following FORMAT:

```
%n %s %b %f %u %g %D %i %h %t %T %X %Y %Z %W %o %C
```

--terse --file-system is equivalent to the following FORMAT:

```
%n %i %l %t %s %S %b %f %a %c %d
```

NOTE: your shell may have its own version of stat, which usually supersedes the version described here. Please refer to your shell's documentation for details about the options it supports.

AUTHOR

Written by Michael Meskes.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report stat translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

stat(2), statfs(2)

Full documentation at: <<https://www.gnu.org/software/coreutils/stat>>

or available locally via: info '(coreutils) stat invocation'

