



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'strndup.3'***

**C:\>man strndup.3**

STRDUP(3)                   Linux Programmer's Manual                   STRDUP(3)

### NAME

strdup, strndup, strdupa, strndupa - duplicate a string

### SYNOPSIS

```
#include <string.h>
```

```
char *strdup(const char *s);
```

```
char *strndup(const char *s, size_t n);
```

```
char *strdupa(const char *s);
```

```
char *strndupa(const char *s, size_t n);
```

Feature Test Macro Requirements for glibc (see [feature\\_test\\_macros\(7\)](#)):

strdup():

```
  _XOPEN_SOURCE >= 500
```

```
  || /* Since glibc 2.12: */ _POSIX_C_SOURCE >= 200809L
```

```
  || /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

strndup():

Since glibc 2.10:

```
  _POSIX_C_SOURCE >= 200809L
```

Before glibc 2.10:

```
  _GNU_SOURCE
```

strdupa(), strndupa(): \_GNU\_SOURCE

### DESCRIPTION

The `strdup()` function returns a pointer to a new string which is a duplicate of the

string s. Memory for the new string is obtained with malloc(3), and can be freed with free(3).

The strndup() function is similar, but copies at most n bytes. If s is longer than n, only n bytes are copied, and a terminating null byte ('\0') is added.

strdupa() and strndupa() are similar, but use alloca(3) to allocate the buffer.

They are available only when using the GNU GCC suite, and suffer from the same limitations described in alloca(3).

## RETURN VALUE

On success, the strdup() function returns a pointer to the duplicated string. It returns NULL if insufficient memory was available, with errno set to indicate the cause of the error.

## ERRORS

ENOMEM Insufficient memory available to allocate duplicate string.

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface                   ? Attribute   ? Value   ?

??

?strdup(), strndup(), strdupa(), ? Thread safety ? MT-Safe ?

?strndupa()                   ?           ?           ?

??

## CONFORMING TO

strdup() conforms to SVr4, 4.3BSD, POSIX.1-2001. strndup() conforms to POSIX.1-2008. strdupa() and strndupa() are GNU extensions.

## SEE ALSO

alloca(3), calloc(3), free(3), malloc(3), realloc(3), string(3), wcsdup(3)

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.