



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-backlight@.service.8'***

**C:\>man systemd-backlight@.service.8**

SYSTEMD-BACKLIGHT@.SERVICE(8) systemd-backlight@.service SYSTEMD-BACKLIGHT@.SERVICE(8)

### NAME

systemd-backlight@.service, systemd-backlight - Load and save the display backlight  
brightness at boot and shutdown

### SYNOPSIS

systemd-backlight@.service  
/lib/systemd/systemd-backlight

### DESCRIPTION

systemd-backlight@.service is a service that restores the display backlight brightness at early boot and saves it at shutdown. On disk, the backlight brightness is stored in /var/lib/systemd/backlight/. During loading, if the udev property ID\_BACKLIGHT\_CLAMP is not set to false, the brightness is clamped to a value of at least 1 or 5% of maximum brightness, whichever is greater. This restriction will be removed when the kernel allows user space to reliably set a brightness value which does not turn off the display.

### KERNEL COMMAND LINE

systemd-backlight understands the following kernel command line parameter:  
systemd.restore\_state=

Takes a boolean argument. Defaults to "1". If "0", does not restore the  
backlight settings on boot. However, settings will still be stored on shutdown.

### SEE ALSO

systemd(1)

