



Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-id128.1'

C:\>man systemd-id128.1

SYSTEMD-ID128(1) systemd-id128 SYSTEMD-ID128(1)

NAME

systemd-id128 - Generate and print sd-128 identifiers

SYNOPSIS

systemd-id128 [OPTIONS...] new

systemd-id128 [OPTIONS...] machine-id

systemd-id128 [OPTIONS...] boot-id

systemd-id128 [OPTIONS...] invocation-id

DESCRIPTION

id128 may be used to conveniently print sd-id128(3) UUIDs. What identifier is printed depends on the specific verb.

With new, a new random identifier will be generated.

With machine-id, the identifier of the current machine will be printed. See machine-id(5).

With `boot-id`, the identifier of the current boot will be printed.

Both `machine-id` and `boot-id` may be combined with the `--app-specific=app-id` switch to generate application-specific IDs. See `sd_id128_get_machine(3)` for the discussion when this is useful.

With `invocation-id`, the identifier of the current service invocation will be printed. This is available in `systemd` services. See `systemd.exec(5)`.

With `show`, well-known UUIDs are printed. When no arguments are specified, all known UUIDs are shown. When arguments are specified, they must be the names or values of one or more known UUIDs, which are then printed.

OPTIONS

The following options are understood:

`-p, --pretty`

Generate output as programming language snippets.

`-a app-id, --app-specific=app-id`

With this option, an identifier that is the result of hashing the application identifier `app-id` and the machine identifier will be printed. The `app-id` argument must be a valid `sd-id128` string identifying the application.

`-u, --uuid`

Generate output as an UUID formatted in the "canonical representation", with five groups of digits separated by hyphens. See the [wikipedia\[1\]](#) for more discussion.

`-h, --help`

Print a short help text and exit.

--version

Print a short version string and exit.

EXIT STATUS

On success, 0 is returned, a non-zero failure code otherwise.

SEE ALSO

systemd(1), sd-id128(3), sd_id128_get_machine(3)

NOTES

1. wikipedia

https://en.wikipedia.org/wiki/Universally_unique_identifier#Format

systemd 245

SYSTEMD-ID128(1)