



Rocky Enterprise Linux 9.2 Manual Pages on command 'tc-taprio.8'

C:\>man tc-taprio.8

TAPRIO(8) Linux TAPRIO(8)

NAME

TAPRIO - Time Aware Priority Shaper

SYNOPSIS

```
tc qdisc ... dev dev parent classid [ handle major: ] taprio num_tc tcs
    map P0 P1 P2 ... queues count1@offset1 count2@offset2 ...
    base-time base-time clockid clockid
    sched-entry <command 1> <gate mask 1> <interval 1>
    sched-entry <command 2> <gate mask 2> <interval 2>
    sched-entry <command 3> <gate mask 3> <interval 3>
    sched-entry <command N> <gate mask N> <interval N>
```

DESCRIPTION

The TAPRIO qdisc implements a simplified version of the scheduling state machine defined by IEEE 802.1Q-2018 Section 8.6.9, which allows configuration of a sequence of gate states, where each gate state allows outgoing traffic for a subset (potentially empty) of traffic classes.

How traffic is mapped to different hardware queues is similar to mqprio(8) and so the map and queues parameters have the same meaning.

The other parameters specify the schedule, and at what point in time it should start (it can behave as the schedule started in the past).

PARAMETERS

num_tc Number of traffic classes to use. Up to 16 classes supported.

map

The priority to traffic class map. Maps priorities 0..15 to a specified traffic class. See `mcprio(8)` for more details.

queues

Provide count and offset of queue range for each traffic class. In the format, `count@offset`. Queue ranges for each traffic classes cannot overlap and must be a contiguous range of queues.

base-time

Specifies the instant in nanoseconds, using the reference of `clockid`, defining the time when the schedule starts. If 'base-time' is a time in the past, the schedule will start at $\text{base-time} + (N * \text{cycle-time})$ where N is the smallest integer so the resulting time is greater than "now", and "cycle-time" is the sum of all the intervals of the entries in the schedule;

clockid

Specifies the clock to be used by `qdisc`'s internal timer for measuring time and scheduling events.

sched-entry

There may be multiple `sched-entry` parameters in a single schedule. Each one has the `sched-entry <command> <gatemask> <interval>` format. The only supported `<command>` is "S", which means "SetGateStates", following the IEEE 802.1Q-2018 definition (Table 8-7). `<gate mask>` is a bit mask where each bit is associated with a traffic class, so bit 0 (the least significant bit) being "on" means that traffic class 0 is "active" for that schedule entry. `<interval>` is a time duration, in nanoseconds, that specifies for how long that state defined by `<command>` and `<gate mask>` should be held before moving to the next entry.

flags

Specifies different modes for `taprio`. Currently, only `txtime-assist` is supported which can be enabled by setting it to 0x1. In this mode, `taprio` will set the transmit timestamp depending on the interval in which the packet

needs to be transmitted. It will then utilize the etf(8) qdisc to sort and transmit the packets at the right time. The second example can be used as a reference to configure this mode.

txtime-delay

This parameter is specific to the txtime offload mode. It specifies the maximum time a packet might take to reach the network card from the taprio qdisc. The value should always be greater than the delta specified in the etf(8) qdisc.

EXAMPLES

The following example shows how a traffic schedule with three traffic classes ("num_tc 3"), which are separated different traffic classes, we are going to call these TC 0, TC 1 and TC 2. We could read the "map" parameter below as: traffic with priority 3 is classified as TC 0, priority 2 is classified as TC 1 and the rest is classified as TC 2.

The schedule will start at instant 1528743495910289987 using the reference CLOCK_TAI. The schedule is composed of three entries each of 300us duration.

```
# tc qdisc replace dev eth0 parent root handle 100 taprio \  
    num_tc 3 \  
    map 2 2 1 0 2 2 2 2 2 2 2 2 2 2 2 2 \  
    queues 1@0 1@1 2@2 \  
    base-time 1528743495910289987 \  
    sched-entry S 01 300000 \  
    sched-entry S 02 300000 \  
    sched-entry S 04 300000 \  
    clockid CLOCK_TAI
```

Following is an example to enable the txtime offload mode in taprio. See etf(8) for more information about configuring the ETF qdisc.

```
# tc qdisc replace dev eth0 parent root handle 100 taprio \  
    num_tc 3 \  
    map 2 2 1 0 2 2 2 2 2 2 2 2 2 2 2 2 \  
    queues 1@0 1@0 1@0 \  
    base-time 1528743495910289987 \  
    sched-entry S 01 300000 \  
    clockid CLOCK_TAI
```

sched-entry S 02 300000 \

sched-entry S 04 400000 \

flags 0x1 \

txtime-delay 200000 \

clockid CLOCK_TAI

tc qdisc replace dev \$IFACE parent 100:1 etf skip_skb_check \

offload delta 200000 clockid CLOCK_TAI

AUTHORS

Vinicius Costa Gomes <vinicius.gomes@intel.com>

iproute2

25 Sept 2018

TAPRIO(8)