



Rocky Enterprise Linux 9.2 Manual Pages on command 'tipc-media.8'

C:\>man tipc-media.8

TIPC-MEDIA(8) Linux TIPC-MEDIA(8)

NAME

tipc-media - list or modify media properties

SYNOPSIS

tipc media set { priority PRIORITY | tolerance TOLERANCE | window WINDOW } media

MEDIA

tipc media get { priority | tolerance | window } media MEDIA

tipc media list

OPTIONS

Options (flags) that can be passed anywhere in the command chain.

-h, --help

Show help about last valid command. For example tipc media --help will show

media help and tipc --help will show general help. The position of the op?

tion in the string is irrelevant.

DESCRIPTION

Media properties

priority

Default link priority inherited by all bearers subsequently enabled on a me?

dia. For more info about link priority see tipc-link(8)

tolerance

Default link tolerance inherited by all bearers subsequently enabled on a

media. For more info about link tolerance see tipc-link(8)

window

Default link window inherited by all bearers subsequently enabled on a me?

dia. For more info about link window see `tipc-link(8)`

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

`tipc(8)`, `tipc-bearer(8)`, `tipc-link(8)`, `tipc-nametable(8)`, `tipc-node(8)`, `tipc-peer(8)`, `tipc-socket(8)`

REPORTING BUGS

Report any bugs to the Network Developers mailing list `<netdev@vger.kernel.org>` where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

AUTHOR

Richard Alpe `<richard.alpe@ericsson.com>`

iproute2

02 Jun 2015

TIPC-MEDIA(8)