



Rocky Enterprise Linux 9.2 Manual Pages on command 'tipc-peer.8'

C:\>man tipc-peer.8

TIPC-PEER(8) Linux TIPC-PEER(8)

NAME

tipc-peer - modify peer information

SYNOPSIS

tipc peer remove address ADDRESS

OPTIONS

Options (flags) that can be passed anywhere in the command chain.

-h, --help

Show help about last valid command. For example `tipc peer --help` will show peer help and `tipc --help` will show general help. The position of the option in the string is irrelevant.

DESCRIPTION

Peer remove

Remove an offline peer node from the local data structures. The peer is identified by its address

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

`tipc(8)`, `tipc-bearer(8)`, `tipc-link(8)`, `tipc-media(8)`, `tipc-nametable(8)`, `tipc-node(8)`, `tipc-socket(8)`

REPORTING BUGS

Report any bugs to the Network Developers mailing list <netdev@vger.kernel.org>

where the development and maintenance is primarily done. You do not have to be
subscribed to the list to send a message there.

AUTHOR

Richard Alpe <richard.alpe@ericsson.com>

iproute2

04 Dec 2015

TIPC-PEER(8)