



Rocky Enterprise Linux 9.2 Manual Pages on command 'tty_ioctl.4'

C:\>man tty_ioctl.4

IOCTL_TTY(2) Linux Programmer's Manual IOCTL_TTY(2)

NAME

ioctl_tty - ioctls for terminals and serial lines

SYNOPSIS

```
#include <termios.h>
```

```
int ioctl(int fd, int cmd, ...);
```

DESCRIPTION

The `ioctl(2)` call for terminals and serial ports accepts many possible command arguments. Most require a third argument, of varying type, here called `argp` or `arg`. Use of `ioctl` makes for nonportable programs. Use the POSIX interface described in `termios(3)` whenever possible.

Get and set terminal attributes

TCGETS struct termios *argp

Equivalent to `tcgetattr(fd, argp)`.

Get the current serial port settings.

TCSETS const struct termios *argp

Equivalent to `tcsetattr(fd, TCSANOW, argp)`.

Set the current serial port settings.

TCSETSW const struct termios *argp

Equivalent to `tcsetattr(fd, TCSADRAIN, argp)`.

Allow the output buffer to drain, and set the current serial port settings.

TCSETSF const struct termios *argp

Equivalent to `tcsetattr(fd, TCSAFLUSH, argp)`.

Allow the output buffer to drain, discard pending input, and set the current serial port settings.

The following four `ioctl`s are just like `TCGETS`, `TCSETS`, `TCSETSW`, `TCSETSF`, except that they take a `struct termio *` instead of a `struct termios *`.

`TCGETA` `struct termio *argp`

`TCSETA` `const struct termio *argp`

`TCSETAW` `const struct termio *argp`

`TCSETAF` `const struct termio *argp`

Locking the `termios` structure

The `termios` structure of a terminal can be locked. The lock is itself a `termios` structure, with nonzero bits or fields indicating a locked value.

`TIOCGLOCKTRMIO` `struct termios *argp`

Gets the locking status of the `termios` structure of the terminal.

`TIOCSLOCKTRMIO` `const struct termios *argp`

Sets the locking status of the `termios` structure of the terminal. Only a process with the `CAP_SYS_ADMIN` capability can do this.

Get and set window size

Window sizes are kept in the kernel, but not used by the kernel (except in the case of virtual consoles, where the kernel will update the window size when the size of the virtual console changes, for example, by loading a new font).

The following constants and structure are defined in `<sys/ioctl.h>`.

`TIOCGWINSZ` `struct winsize *argp`

Get window size.

`TIOCSWINSZ` `const struct winsize *argp`

Set window size.

The `struct` used by these `ioctl`s is defined as

```
struct winsize {
    unsigned short ws_row;
    unsigned short ws_col;
    unsigned short ws_xpixel; /* unused */
    unsigned short ws_ypixel; /* unused */
};
```

When the window size changes, a SIGWINCH signal is sent to the foreground process group.

Sending a break

TCSBRK int arg

Equivalent to tcsendbreak(fd, arg).

If the terminal is using asynchronous serial data transmission, and arg is zero, then send a break (a stream of zero bits) for between 0.25 and 0.5 seconds. If the terminal is not using asynchronous serial data transmission, then either a break is sent, or the function returns without doing anything. When arg is nonzero, nobody knows what will happen.

(SVr4, UnixWare, Solaris, Linux treat tcsendbreak(fd, arg) with nonzero arg like tcdrain(fd). SunOS treats arg as a multiplier, and sends a stream of bits arg times as long as done for zero arg. DG/UX and AIX treat arg (when nonzero) as a time interval measured in milliseconds. HP-UX ignores arg.)

TCSBRKP int arg

So-called "POSIX version" of TCSBRK. It treats nonzero arg as a time interval measured in deciseconds, and does nothing when the driver does not support breaks.

TIOCSBRK void

Turn break on, that is, start sending zero bits.

TIOCCBRK void

Turn break off, that is, stop sending zero bits.

Software flow control

TCXONC int arg

Equivalent to tcflow(fd, arg).

See tcflow(3) for the argument values TCOOFF, TCOON, TCIOFF, TCION.

Buffer count and flushing

FIONREAD int *argp

Get the number of bytes in the input buffer.

TIOCINQ int *argp

Same as FIONREAD.

TIOCOUTQ int *argp

Get the number of bytes in the output buffer.

TCFLSH int arg

Equivalent to `tflush(fd, arg)`.

See `tflush(3)` for the argument values `TCIFLUSH`, `TCOFLUSH`, `TCIOFLUSH`.

Faking input

TIOCSTI const char *argp

Insert the given byte in the input queue.

Redirecting console output

TIOCCONS void

Redirect output that would have gone to `/dev/console` or `/dev/tty0` to the given terminal. If that was a pseudoterminal master, send it to the slave.

In Linux before version 2.6.10, anybody can do this as long as the output was not redirected yet; since version 2.6.10, only a process with the `CAP_SYS_ADMIN` capability may do this. If output was redirected already `EBUSY` is returned, but redirection can be stopped by using this `ioctl` with `fd` pointing at `/dev/console` or `/dev/tty0`.

Controlling terminal

TIOCSTTY int arg

Make the given terminal the controlling terminal of the calling process.

The calling process must be a session leader and not have a controlling terminal already. For this case, `arg` should be specified as zero.

If this terminal is already the controlling terminal of a different session group, then the `ioctl` fails with `EPERM`, unless the caller has the `CAP_SYS_ADMIN` capability and `arg` equals 1, in which case the terminal is stolen, and all processes that had it as controlling terminal lose it.

TIOCNOTTY void

If the given terminal was the controlling terminal of the calling process, give up this controlling terminal. If the process was session leader, then send `SIGHUP` and `SIGCONT` to the foreground process group and all processes in the current session lose their controlling terminal.

Process group and session ID

TIOCGPGRP pid_t *argp

When successful, equivalent to `*argp = tcgetpgrp(fd)`.

Get the process group ID of the foreground process group on this terminal.

TIOCSPGRP const pid_t *argp

Equivalent to tcsetpgrp(fd, *argp).

Set the foreground process group ID of this terminal.

TIOCGSID pid_t *argp

Get the session ID of the given terminal. This fails with the error ENOTTY if the terminal is not a master pseudoterminal and not our controlling terminal. Strange.

Exclusive mode

TIOCEXCL void

Put the terminal into exclusive mode. No further open(2) operations on the terminal are permitted. (They fail with EBUSY, except for a process with the CAP_SYS_ADMIN capability.)

TIOCGEXCL int *argp

(since Linux 3.8) If the terminal is currently in exclusive mode, place a nonzero value in the location pointed to by argp; otherwise, place zero in *argp.

TIOCNXCL void

Disable exclusive mode.

Line discipline

TIOCGETD int *argp

Get the line discipline of the terminal.

TIOCSETD const int *argp

Set the line discipline of the terminal.

Pseudoterminal ioctls

TIOCPKT const int *argp

Enable (when *argp is nonzero) or disable packet mode. Can be applied to the master side of a pseudoterminal only (and will return ENOTTY otherwise).

In packet mode, each subsequent read(2) will return a packet that either contains a single nonzero control byte, or has a single byte containing zero (' ') followed by data written on the slave side of the pseudoterminal. If the first byte is not TIOCPKT_DATA (0), it is an OR of one or more of the following bits:

TIOCPKT_FLUSHREAD The read queue for the terminal is flushed.

TIOCPKT_FLUSHWRITE The write queue for the terminal is flushed.

TIOCPKT_STOP Output to the terminal is stopped.

TIOCPKT_START Output to the terminal is restarted.

TIOCPKT_DOSTOP The start and stop characters are ^S/^Q.

TIOCPKT_NOSTOP The start and stop characters are not ^S/^Q.

While this mode is in use, the presence of control status information to be read from the master side may be detected by a `select(2)` for exceptional conditions or a `poll(2)` for the `POLLPRI` event.

This mode is used by `rlogin(1)` and `rlogind(8)` to implement a remote-echoed, locally ^S/^Q flow-controlled remote login.

`TIOCGPKT` `const int *argp`

(since Linux 3.8) Return the current packet mode setting in the integer pointed to by `argp`.

`TIOCSPTLCK` `int *argp`

Set (if `*argp` is nonzero) or remove (if `*argp` is zero) the pseudoterminal slave device. (See also `unlockpt(3)`.)

`TIOCGPTLCK` `int *argp`

(since Linux 3.8) Place the current lock state of the pseudoterminal slave device in the location pointed to by `argp`.

`TIOCGPTPEER` `int flags`

(since Linux 4.13) Given a file descriptor in `fd` that refers to a pseudoterminal master, open (with the given `open(2)`-style flags) and return a new file descriptor that refers to the peer pseudoterminal slave device. This operation can be performed regardless of whether the pathname of the slave device is accessible through the calling process's mount namespace.

Security-conscious programs interacting with namespaces may wish to use this operation rather than `open(2)` with the pathname returned by `ptsname(3)`, and similar library functions that have insecure APIs. (For example, confusion can occur in some cases using `ptsname(3)` with a pathname where a `devpts` filesystem has been mounted in a different mount namespace.)

The BSD ioctls `TIOCSTOP`, `TIOCSTART`, `TIOCUCNTL`, `TIOCREMOTE` have not been implemented under Linux.

TIOCMGET int *argp

Get the status of modem bits.

TIOCMSET const int *argp

Set the status of modem bits.

TIOCMBIC const int *argp

Clear the indicated modem bits.

TIOCMBIS const int *argp

Set the indicated modem bits.

The following bits are used by the above ioctls:

TIOCM_LE DSR (data set ready/line enable)

TIOCM_DTR DTR (data terminal ready)

TIOCM_RTS RTS (request to send)

TIOCM_ST Secondary TXD (transmit)

TIOCM_SR Secondary RXD (receive)

TIOCM_CTS CTS (clear to send)

TIOCM_CAR DCD (data carrier detect)

TIOCM_CD see TIOCM_CAR

TIOCM_RNG RNG (ring)

TIOCM_RI see TIOCM_RNG

TIOCM_DSR DSR (data set ready)

TIOCMWAIT int arg

Wait for any of the 4 modem bits (DCD, RI, DSR, CTS) to change. The bits of interest are specified as a bit mask in arg, by ORing together any of the bit values, TIOCM_RNG, TIOCM_DSR, TIOCM_CD, and TIOCM_CTS. The caller should use TIOCGICOUNT to see which bit has changed.

TIOCGICOUNT struct serial_icounter_struct *argp

Get counts of input serial line interrupts (DCD, RI, DSR, CTS). The counts are written to the serial_icounter_struct structure pointed to by argp.

Note: both 1->0 and 0->1 transitions are counted, except for RI, where only 0->1 transitions are counted.

Marking a line as local

TIOCGSOFTCAR int *argp

("Get software carrier flag") Get the status of the CLOCAL flag in the

c_cflag field of the termios structure.

TIOCSSOFTCAR const int *argp

("Set software carrier flag") Set the CLOCAL flag in the termios structure when *argp is nonzero, and clear it otherwise.

If the CLOCAL flag for a line is off, the hardware carrier detect (DCD) signal is significant, and an open(2) of the corresponding terminal will block until DCD is asserted, unless the O_NONBLOCK flag is given. If CLOCAL is set, the line behaves as if DCD is always asserted. The software carrier flag is usually turned on for local devices, and is off for lines with modems.

Linux-specific

For the TIOCLINUX ioctl, see ioctl_console(2).

Kernel debugging

```
#include <linux/tty.h>
```

TIOCTTYGSTRUCT struct tty_struct *argp

Get the tty_struct corresponding to fd. This command was removed in Linux 2.5.67.

RETURN VALUE

The ioctl(2) system call returns 0 on success. On error, it returns -1 and sets errno appropriately.

ERRORS

EINVAL Invalid command parameter.

ENOIOCTLCMD

Unknown command.

ENOTTY Inappropriate fd.

EPERM Insufficient permission.

EXAMPLE

Check the condition of DTR on the serial port.

```
#include <termios.h>
```

```
#include <fcntl.h>
```

```
#include <sys/ioctl.h>
```

```
int
```

```
main(void)
```

```
{
```

```
int fd, serial;

fd = open("/dev/ttyS0", O_RDONLY);

ioctl(fd, TIOCMGET, &serial);

if (serial & TIOCM_DTR)

    puts("TIOCM_DTR is set");

else

    puts("TIOCM_DTR is not set");

close(fd);

}
```

SEE ALSO

ldattach(1), ioctl(2), ioctl_console(2), termios(3), pty(7)

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.