



Rocky Enterprise Linux 9.2 Manual Pages on command 'udisks2.conf.5'

C:\>man udisks2.conf.5

UDISKS2.CONF(5) UDisks Daemon Configuration UDISKS2.CONF(5)

NAME

udisks2.conf - The udisks2 configuration file

DESCRIPTION

The udisks project provides additional functionality via pluggable modules. These plugins can be inserted into the daemon either by D-Bus call `org.freedesktop.UDisks2.Manager.EnableModules()` or by running the udisks daemon with `--force-load-modules` command line option.

It is also possible to configure the modules loading behavior via the configuration file placed at `/etc/udisks/udisks2.conf`.

CONFIGURATION FILE

The default configuration file `udisks2.conf` looks like this:

```
[udisks2]
modules=*
modules_load_preference=ondemand
[defaults]
encryption=luks1
```

`modules = <string list>`

This variable controls what modules should be loaded. It may contain either a comma-separated list of modules to load or a single asterisk which stands for all the modules.

`modules_load_preference = ondemand|onstartup`

This key tells `udisksd` when to load the plugins: either at startup or on demand by D-Bus `org.freedesktop.UDisks2.Manager.EnableModules()`.

`encryption = luks1|luks2`

This variable controls which encryption technology will be used by default when creating an encrypted filesystem.

AUTHOR

<phatina@redhat.com>

BUGS

Please send bug reports to either the distribution bug tracker or the upstream bug tracker at <https://github.com/storaged-project/udisks/issues>.

SEE ALSO

`udisks(8)`, `udisksctl(1)`, `umount.udisks2(8)`

`udisks2.conf` 2.8.4

August 2018

UDISKS2.CONF(5)