



Rocky Enterprise Linux 9.2 Manual Pages on command 'unmkinitramfs.8'

C:~>man unmkinitramfs.8

UNMKINITRAMFS(8) System Administration UNMKINITRAMFS(8)

NAME

unmkinitramfs - extract content from an initramfs image

SYNOPSIS

unmkinitramfs [-v] initramfs-file directory

unmkinitramfs -h

DESCRIPTION

The `unmkinitramfs` command extracts the content of a given initramfs image using `cpio`. If the image contains multiple segments, each are passed to `cpio` in order.

OPTIONS

- h Display usage information and exit.
- v Display verbose messages about extraction.

USAGE EXAMPLES

Extract initramfs content of current running kernel:

```
unmkinitramfs /boot/initrd.img-$(uname -r) initramfs/
```

BUGS

`unmkinitramfs` cannot deal with multiple-segmented initramfs images, except where an early (uncompressed) initramfs with system firmware is prepended to the regular compressed initramfs.

AUTHOR

The `initramfs-tools` are written by Maximilian Attems <maks@debian.org> and numerous others.

SEE ALSO

initramfs-tools(7), lsinitramfs(8), mkinitramfs(8), update-initramfs(8).

initramfs-tools

2016/12/15

UNMKINITRAMFS(8)