



Rocky Enterprise Linux 9.2 Manual Pages on command 'unwrpdiff.1'

C:\>man unwrpdiff.1

UNWRAPDIFF(1) Man pages UNWRAPDIFF(1)

NAME

unwrpdiff - demangle word-wrapped patches

SYNOPSIS

unwrpdiff [-v] [file...]

unwrpdiff [--help] | [--version]}

DESCRIPTION

unwrpdiff demangles patches that have been word-wrapped, in an attempt to make them useful.

The corrected diff is sent to standard output. Note that you will probably need to use the -l option when applying the patch, in order to ignore any whitespace differences there may be.

OPTIONS

-v

Verbose operation. A list of lines that are modified in a way that might be wrong is sent to stderr.

--help

Display a short usage message.

--version

Display the version number of unwrpdiff.

LIMITATIONS

Some heuristics are used to decide whether use a space to recombine a wrapped line,

or just join them together. Currently this is done by comparing with last three characters of a line with the first two characters of its continuation, and using a space if any of them are different.

The patch needs to have been valid before being word-wrapped.

The last line of a hunk is nearly always ambiguous. If the next line begins `?@@?`, `?Index: ?`, `?diff ?` or `?--- ?` then it is taken to be complete; otherwise it is unwrapped using the next line.

AUTHOR

Tim Waugh <twaugh@redhat.com>

Package maintainer

patchutils

17 January 2003

UNWRAPDIFF(1)