



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'update-cracklib.8'***

### **C:\>man update-cracklib.8**

update-cracklib(8)            System Manager's Manual            update-cracklib(8)

#### NAME

update-cracklib - Regenerate cracklib dictionary

#### SYNOPSIS

update-cracklib

#### DESCRIPTION

update-cracklib builds a compressed and accumulated version of wordlists stored in the directories given in cracklib's configuration file `/etc/cracklib/cracklib.conf`.

Programs using cracklib2 need this database to be of any use.

By default this script is called by cron every day.

#### RESULT

update-cracklib prints out two numbers: the number of words read from the ASCII dictionaries and the number of words eventually written into the cracklib database; if no error occurred, these should be equal.

0 is returned on success, otherwise an error message is printed to standard error and -1 is returned.

#### FILES

`/etc/cracklib/cracklib.conf`

shell script that sets `cracklib_dictpath_src` which must be a space separated list of source dictionary files.

#### SEE ALSO

`cracklib(3)`, `crack_mkdict(8)`

## AUTHOR

This program and manual page was written by Martin Pitt <martin@piware.de> for the Debian GNU/Linux System (but may be used by others).

Martin Pitt

June 09, 2003

update-cracklib(8)