



Rocky Enterprise Linux 9.2 Manual Pages on command 'user-dirs.conf.5'

C:\>man user-dirs.conf.5

USER-DIRS.CONF(5) File Formats USER-DIRS.CONF(5)

NAME

user-dirs.conf - configuration for xdg-user-dirs-update

DESCRIPTION

The `/etc/xdg/user-dirs.conf` file is a text file that controls the behavior of the `xdg-user-dirs-update` command. Users can have their own `~/.config/user-dirs.conf` file, which overrides the system-wide configuration.

The following keys are recognised:

`enabled=boolean`

When set to `False`, `xdg-user-dirs-update` will not change the XDG user dirs configuration.

`filename_encoding=encoding`

This sets the filename encoding to use. `encoding` can be an explicit encoding name, such as `UTF-8`, or `"locale"`, which means the encoding of the users locale will be used.

Lines beginning with a `#` character are ignored.

ENVIRONMENT

`XDG_CONFIG_DIRS`

The system-wide `user-dirs.conf` file is located in this directory. The default is `/etc/xdg`.

`XDG_CONFIG_HOME`

The per-user `user-dirs.conf` file is located in this directory. The default is

`$HOME/.config.`

SEE ALSO

`xdg-user-dirs-update(1)`

XDG

`USER-DIRS.CONF(5)`