



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'vhangup.2'***

**C:\>man vhangup.2**

VHANGUP(2)                      Linux Programmer's Manual                      VHANGUP(2)

### NAME

vhangup - virtually hangup the current terminal

### SYNOPSIS

```
#include <unistd.h>
```

```
int vhangup(void);
```

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

`vhangup()`:

Since glibc 2.21:

```
_DEFAULT_SOURCE
```

In glibc 2.19 and 2.20:

```
_DEFAULT_SOURCE || (_XOPEN_SOURCE && _XOPEN_SOURCE < 500)
```

Up to and including glibc 2.19:

```
_BSD_SOURCE || (_XOPEN_SOURCE && _XOPEN_SOURCE < 500)
```

### DESCRIPTION

`vhangup()` simulates a hangup on the current terminal. This call arranges for other users to have a ?clean? terminal at login time.

### RETURN VALUE

On success, zero is returned. On error, -1 is returned, and `errno` is set appropriately.

### ERRORS

**EPERM** The calling process has insufficient privilege to call `vhangup()`; the

CAP\_SYS\_TTY\_CONFIG capability is required.

#### CONFORMING TO

This call is Linux-specific, and should not be used in programs intended to be portable.

#### SEE ALSO

init(1), capabilities(7)

#### COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2016-03-15

VHANGUP(2)