



## Rocky Enterprise Linux 9.2 Manual Pages on command 'wcpbrk.3'

C:\>man wcpbrk.3

WCSPBRK(3)                   Linux Programmer's Manual                   WCSPBRK(3)

### NAME

wcpbrk - search a wide-character string for any of a set of wide characters

### SYNOPSIS

```
#include <wchar.h>
```

```
wchar_t *wcpbrk(const wchar_t *wcs, const wchar_t *accept);
```

### DESCRIPTION

The wcpbrk() function is the wide-character equivalent of the strpbrk(3) function.

It searches for the first occurrence in the wide-character string pointed to by wcs of any of the characters in the wide-character string pointed to by accept.

### RETURN VALUE

The wcpbrk() function returns a pointer to the first occurrence in wcs of any of the characters listed in accept. If wcs contains none of these characters, NULL is returned.

### ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute   ? Value   ?

??

?wcpbrk() ? Thread safety ? MT-Safe ?

??

### CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

#### SEE ALSO

`strpbrk(3)`, `wcschr(3)`, `wcscspn(3)`

#### COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WCSPBRK(3)