



Rocky Enterprise Linux 9.2 Manual Pages on command 'wcstok.3'

C:\>man wcstok.3

WCSTOK(3) Linux Programmer's Manual WCSTOK(3)

NAME

wcstok - split wide-character string into tokens

SYNOPSIS

```
#include <wchar.h>

wchar_t *wcstok(wchar_t *wcs, const wchar_t *delim, wchar_t **ptr);
```

DESCRIPTION

The `wcstok()` function is the wide-character equivalent of the `strtok(3)` function, with an added argument to make it multithread-safe. It can be used to split a wide-character string `wcs` into tokens, where a token is defined as a substring not containing any wide-characters from `delim`.

The search starts at `wcs`, if `wcs` is not `NULL`, or at `*ptr`, if `wcs` is `NULL`. First, any delimiter wide-characters are skipped, that is, the pointer is advanced beyond any wide-characters which occur in `delim`. If the end of the wide-character string is now reached, `wcstok()` returns `NULL`, to indicate that no tokens were found, and stores an appropriate value in `*ptr`, so that subsequent calls to `wcstok()` will continue to return `NULL`. Otherwise, the `wcstok()` function recognizes the beginning of a token and returns a pointer to it, but before doing that, it zero-terminates the token by replacing the next wide-character which occurs in `delim` with a null wide character (`L'\0'`), and it updates `*ptr` so that subsequent calls will continue searching after the end of recognized token.

RETURN VALUE

The `wcstok()` function returns a pointer to the next token, or `NULL` if no further token was found.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`wcstok()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The original `wcs` wide-character string is destructively modified during the operation.

EXAMPLE

The following code loops over the tokens contained in a wide-character string.

```
wchar_t *wcs = ...;
wchar_t *token;
wchar_t *state;
for (token = wcstok(wcs, " \\t\\n", &state);
     token != NULL;
     token = wcstok(NULL, " \\t\\n", &state)) {
    ...
}
```

SEE ALSO

`strtok(3)`, `wcschr(3)`

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.