



Rocky Enterprise Linux 9.2 Manual Pages on command 'whois.conf.5'

C:\>man whois.conf.5

WHOIS.CONF(5) Debian GNU/Linux WHOIS.CONF(5)

NAME

whois.conf - alternative WHOIS servers list for whois client

SYNOPSIS

/etc/whois.conf

DESCRIPTION

This file contains a list of WHOIS servers which can augment or override the built-in list of the client.

It's a plain text file in ASCII encoding. Each line consists of two fields: a pattern to match WHOIS object identifier and a corresponding WHOIS server domain name.

Fields are separated by non-empty sequence of space or a tabular characters. A line starting with a hash character is a free comment and it's not considered.

The pattern is case-insensitive extended regular expression if whois client has been compiled with POSIX regular expressions support. Otherwise, simple case-insensitive suffix comparison against WHOIS object identifier is used.

Internationalized domain names (IDN) must be specified in ascii-compatible encoding (ACE) format.

EXAMPLE

```
\.nz$            nz.whois-servers.net  
  
# Hangul Korean TLD  
  
\.xn--3e0b707e$    whois.kr  
  
# Private ASNs
```

^as645(1[2-9]|2[0-9]|3[0-4])\$ whois.example.net

FILES

/etc/whois.conf

SEE ALSO

whois(1)

AUTHOR

This manual page was written by Petr P?sa? <ppisar@redhat.com> and is licensed under the terms of the GNU General Public License, version 2 or higher.

Petr P?sa?

2019-12-30

WHOIS.CONF(5)