



Rocky Enterprise Linux 9.2 Manual Pages on command 'wmemchr.3'

C:\>man wmemchr.3

WMEMCHR(3) Linux Programmer's Manual WMEMCHR(3)

NAME

wmemchr - search a wide character in a wide-character array

SYNOPSIS

```
#include <wchar.h>

wchar_t *wmemchr(const wchar_t *s, wchar_t c, size_t n);
```

DESCRIPTION

The wmemchr() function is the wide-character equivalent of the memchr(3) function. It searches the n wide characters starting at s for the first occurrence of the wide character c.

RETURN VALUE

The wmemchr() function returns a pointer to the first occurrence of c among the n wide characters starting at s, or NULL if c does not occur among these.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?wmemchr() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

`memchr(3)`, `wcschr(3)`

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WMEMCHR(3)