



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'x11perfcomp.1'***

**C:~>man x11perfcomp.1**

X11PERFCOMP(1)                    General Commands Manual                    X11PERFCOMP(1)

### NAME

x11perfcomp - X11 server performance comparison program

### SYNTAX

x11perfcomp [ -r | -ro ] [ -l label\_file ] files

### DESCRIPTION

The x11perfcomp program merges the output of several x11perf(1) runs into a nice tabular format. It takes the results in each file, fills in any missing test results if necessary, and for each test shows the objects/second rate of each server. If invoked with the -r or -ro options, it shows the relative performance of each server to the first server.

Normally, x11perfcomp uses the first file specified to determine which specific tests it should report on. Some (non-DEC :) servers may fail to perform all tests. In this case, x11perfcomp automatically substitutes in a rate of 0.0 objects/second. Since the first file determines which tests to report on, this file must contain a superset of the tests reported in the other files, else x11perfcomp will fail.

You can provide an explicit list of tests to report on by using the -l switch to specify a file of labels. You can create a label file by using the -label option in x11perf.

### OPTIONS

x11perfcomp accepts the options listed below:

-r Specifies that the output should also include relative server performance.

-ro Specifies that the output should include only relative server performance.

-l label\_file Specifies a label file to use.

#### X DEFAULTS

There are no X defaults used by this program.

#### SEE ALSO

X(7), x11perf(1)

#### AUTHORS

Mark Moraes wrote the original scripts to compare servers.

Joel McCormack just munged them together a bit.

X Version 11

x11perf 1.6.1

X11PERFCOMP(1)