



Rocky Enterprise Linux 9.2 Manual Pages on command 'xdg-desktop-icon.1'

C:\>man xdg-desktop-icon.1

XDG-DESKTOP-ICON(1) xdg-desktop-icon Manual XDG-DESKTOP-ICON(1)

NAME

xdg-desktop-icon - command line tool for (un)installing icons to the desktop

SYNOPSIS

xdg-desktop-icon install [--novendor] FILE

xdg-desktop-icon uninstall FILE

xdg-desktop-icon {--help | --manual | --version}

DESCRIPTION

The xdg-desktop-icon program can be used to install an application launcher or other file on the desktop of the current user.

An application launcher is represented by a *.desktop file. Desktop files are defined by the freedesktop.org Desktop Entry Specification. The most important aspects of *.desktop files are summarized below.

COMMANDS

install

Installs FILE to the desktop of the current user. FILE can be a *.desktop file or any other type of file.

uninstall

Removes FILE from the desktop of the current user.

OPTIONS

--novendor

Normally, xdg-desktop-icon checks to ensure that a *.desktop file to be

installed has a vendor prefix. This option can be used to disable that check.

A vendor prefix consists of alpha characters ([a-zA-Z]) and is terminated with a dash ("-"). Companies and organizations are encouraged to use a word or phrase, preferably the organizations name, for which they hold a trademark as their vendor prefix. The purpose of the vendor prefix is to prevent name conflicts.

--help

Show command synopsis.

--manual

Show this manual page.

--version

Show the xdg-utils version information.

DESKTOP FILES

An application launcher can be added to the desktop by installing a *.desktop file.

A *.desktop file consists of a [Desktop Entry] header followed by several Key=Value lines.

A *.desktop file can provide a name and description for an application in several different languages. This is done by adding a language code as used by LC_MESSAGES in square brackets behind the Key. This way one can specify different values for the same Key depending on the currently selected language.

The following keys are often used:

Type=Application

This is a mandatory field that indicates that the *.desktop file describes an application launcher.

Name=Application Name

The name of the application. For example Mozilla

GenericName=Generic Name

A generic description of the application. For example Web Browser

Comment=Comment

Optional field to specify a tooltip for the application. For example Visit websites on the Internet

Icon=Icon File

The icon to use for the application. This can either be an absolute path to an

image file or an icon-name. If an icon-name is provided an image lookup by name is done in the user's current icon theme. The `xdg-icon-resource` command can be used to install image files into icon themes. The advantage of using an icon-name instead of an absolute path is that with an icon-name the application icon can be provided in several different sizes as well as in several differently themed styles.

Exec=Command Line

The command line to start the application. If the application can open files the `%f` placeholder should be specified. When a file is dropped on the application launcher the `%f` is replaced with the file path of the dropped file.

If multiple files can be specified on the command line the `%F` placeholder should be used instead of `%f`. If the application is able to open URLs in addition to local files then `%u` or `%U` can be used instead of `%f` or `%F`.

For a complete overview of the `*.desktop` file format please visit

<http://www.freedesktop.org/wiki/Specifications/desktop-entry-spec>

ENVIRONMENT VARIABLES

`xdg-desktop-icon` honours the following environment variables:

`XDG_UTILS_DEBUG_LEVEL`

Setting this environment variable to a non-zero numerical value makes `xdg-desktop-icon` do more verbose reporting on `stderr`. Setting a higher value increases the verbosity.

EXIT CODES

An exit code of 0 indicates success while a non-zero exit code indicates failure.

The following failure codes can be returned:

1

Error in command line syntax.

2

One of the files passed on the command line did not exist.

3

A required tool could not be found.

4

The action failed.

5

No permission to read one of the files passed on the command line.

SEE ALSO

`xdg-icon-resource(1)`

EXAMPLES

The company ShinyThings Inc. has developed an application named "WebMirror" and would like to add a launcher for for on the desktop. The company will use "shinythings" as its vendor id. In order to add the application to the desktop there needs to be a .desktop file for the application:

shinythings-webmirror.desktop:

```
[Desktop Entry]
```

```
Encoding=UTF-8
```

```
Type=Application
```

```
Exec=webmirror
```

```
Icon=shinythings-webmirror
```

```
Name=WebMirror
```

```
Name[nl]=WebSpiegel
```

Now the `xdg-desktop-icon` tool can be used to add the `webmirror.desktop` file to the desktop:

```
xdg-desktop-icon install ./shinythings-webmirror.desktop
```

To add a README file to the desktop as well, the following command can be used:

```
xdg-desktop-icon install ./shinythings-README
```

AUTHORS

Kevin Krammer

Author.

Jeremy White

Author.

COPYRIGHT

Copyright ? 2006

xdg-utils 1.0

01/11/2021

XDG-DESKTOP-ICON(1)