



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Add-AppvPublishingServer'

PS C:\Users\wahid> Get-Help Add-AppvPublishingServer

NAME

Add-AppvPublishingServer

SYNOPSIS

Adds a publishing server for the computer that runs the App-V client.

SYNTAX

```
Add-AppvPublishingServer [-Name] <String> [-URL] <String>  
[[[-GlobalRefreshEnabled] <Boolean>] [[-GlobalRefreshOnLogon] <Boolean>]  
[[[-GlobalRefreshInterval] <UInt32>] [[-GlobalRefreshIntervalUnit] {Hour |  
Day}]] [[-UserRefreshEnabled] <Boolean>] [[-UserRefreshOnLogon] <Boolean>]  
[[[-UserRefreshInterval] <UInt32>] [[-UserRefreshIntervalUnit] {Hour | Day}]]  
[<CommonParameters>]
```

DESCRIPTION

The Add-AppvPublishingServer cmdlet adds a new publishing server for the computer that runs the Microsoft Application Virtualization (App-V) client to connect to. After the server has been added, the computer that runs the App-V client can use the server to obtain publishing refresh data, stream packages,

and perform other operations.

PARAMETERS

-GlobalRefreshEnabled <Boolean>

Specifies whether to turn on the refreshing of the publishing server for all packages that are published globally. You can set the refresh to be at the time of logon or on a defined time interval.

-GlobalRefreshInterval <UInt32>

Specifies the time interval for the refresh of globally published packages.

-GlobalRefreshIntervalUnit <IntervalUnit>

Specifies the unit of time measurement. The acceptable values for this parameter are: day and hour.

-GlobalRefreshOnLogon <Boolean>

Specifies whether a refresh of all packages published to globally occurs every time that a user logs into the target computer.

-Name <String>

Specifies the friendly name of the publishing server.

-URL <String>

Specifies the URL path of the App-V publishing server.

-UserRefreshEnabled <Boolean>

Specifies whether to turn on the refreshing of the publishing server for all packages that are published to the user. The refresh can be set to be at the time of logon or on a defined time interval.

-UserRefreshInterval <UInt32>

Specifies the time interval for refreshes of user-published packages.

-UserRefreshIntervalUnit <IntervalUnit>

Specifies the unit of time measurement. The acceptable values for this parameter are: day and hour.

-UserRefreshOnLogon <Boolean>

Specifies whether a refresh of all packages published to the user occurs every time that a user logs into the target computer.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

REMARKS

To see the examples, type: "get-help Add-AppvPublishingServer -examples".

For more information, type: "get-help Add-AppvPublishingServer -detailed".

For technical information, type: "get-help Add-AppvPublishingServer -full".

For online help, type: "get-help Add-AppvPublishingServer -online"